BLUE MONSTER Products

Blue Monster Stay-Soft Thread Sealant with PTFE

Specially formulated for residential and commercial fire sprinkler systems

Blue Monster Stay-Soft PTFE enriched pipe thread compound does not harden and allows for pre-fab application to threads weeks before system assembly and pressurization. Stay-Soft is non-seizing and allows for easy disassembly of any threaded connection years after assembly. Easy clean-up and indefinite shelf life.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
76023	1/4 pint / 4 fl. oz. / 118 ml	24	18 lbs (8.2 kg)
76025	1/2 pint / 8 fl. oz. / 237 ml	24	26 lbs (11.8 kg)
76027	1 pint / 16 fl. oz. / 473 ml	12	25 lbs (11.3 kg)
76029	1 quart / 32 fl. oz. / .95 liter	12	50 lbs (22.7 kg)

Approved for use on all metal threaded connections, FlowGuard Gold®, Blazemaster®, and Corzan® pipe and fittings.

FBC SYSTEM COMPATIBLE

Meets Mil. Spec. TT-S-1732
Temperature range: -15ºF (-20ºC) to +400ºF (204ºC)
Pressure ratings: Gases up to 5,000 PSI (351.5 kg/cm²)
Liquids up to 10,000 PSI (703.1 kg/cm²)

Blue Monster Industrial Grade Thread Sealant

BLUE MONSTER Industrial Grade Pipe Thread Compound is a slow-drying, soft-setting, non-hardening pipe thread compound. Specially formulated with superb "sticking" characteristics, BLUE MONSTER applies evenly and quickly to threads. Recommended for on-site or assembly line work, BLUE MONSTER is lead-free, non-toxic and will not harden or separate in the can.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
76007	2 fl. oz. Squeeze Tube	24	4 lbs.
76009	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76011	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76015	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76019	1 quart / 32 fl. oz. / .95 liter	12	48 lbs.

Meets Mil. Spec. TT-S-1732
Temperature range: -50ºF (-45ºC) to +400ºF (204ºC)
Pressure ratings: Gases up to 3,000 PSI (211 kg/cm²)
Liquids up to 6,000 PSI (422 kg/cm²)
Not recommended for use on oxygen systems.
Use Clean-Fit *3-wrap* Oxygen PTFE Tape.

NSF pw/dwv/sw Standard 14 Standard 61

Blue Monster Industrial Grade Thread Sealant with PTFE

Formulated for extra lubrication on metal pipe threads, BLUE MONSTER Industrial Grade Thread Sealant with PTFE is a slow-drying, soft-setting, non-hardening pipe thread compound. BLUE MONSTER has a high bulk density, which means there are more solids in the formulation. Recommended for on-site or assembly line work. It is lead-free, non-toxic and will not harden or separate in the can.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
76000	2 fl. oz. Squeeze Tube	24	4 lbs.
76001	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76003	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76005	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76017	1 quart / 32 fl. oz. / .95 liter	12	48 lbs.

Meets Mil. Spec. TT-S-1732
Temperature range: -50ºF (-45ºC) to +400ºF (204ºC)
Pressure ratings: Gases up to 3,000 PSI (211 kg/cm²)
Liquids up to 10,000 PSI (703.1 kg/cm²)
Not recommended for use on oxygen systems.
Use Clean-Fit *3-wrap* Oxygen PTFE Tape.

C SP US ANSI LC7-2009 NSF pw/dwv/sw Standard 14 Standard 61

Food-Grade Anti-Seize Lubricant

Blue Monster Food-grade Anti-Seize is a premium grade lubricant made of ingredients meeting FDA requirements and designed for use where incidental food contact is possible. This lubricant maintains its anti-seize capabilities at high and low temperatures, and allows for easy disassembly. Protects against seizing up to 1800°F. Avoid direct contact to food during the application of this product.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
76048	Net Wt. 9 oz. (255 g.)	12	10.0 lbs.
76050	Net Wt. 18 oz. (510 g.)	12	20.0 lbs.

Applications: Food processing machinery to lubricate stainless steel fittings, bushings, flanges, headers, nuts, screws, studs, threaded surfaces, pipes, plugs, and manifolds to prevent seizing and galling of surfaces. Not for use on oxygen.

NSF Nonfood Compounds H1