SCI
An ASC Engineered Solution

QuickBite™

No special tools required. No gluing, crimping or soldering required.

LEAD FREE

QuickBite™ valves and fittings are the simplest connectors to use.

1 - Clean the tube
2 - Press on the QuickBite™ fitting or valve
3 - DONE! No leak seal

QuickBite™ Quick Facts:

- Fittings certified to 200 PSI and 180° F
- Works with PEX, CPVC and copper tubing
- PEX stiffener pre-installed - Easy to remove for PVC or Copper installations
- Lead-free brass
- Full flow
- Fittings & valves are removable and reusable
- Easy-to-follow instructions are available at www.smithcooper.com/QR1 or by scanning the QR code on the back of every bag



Fig. QBBV - Valve

Size in	Part Number	Packing		Weight lb
		Inner	Master	
1/2	QBBV004	10	20	0.408
3/4	QBBV006	10	20	0.598
1	QBBV010	5	10	1.152

Fig. 36X 1L – Cross



Size in	Part Number	A in	Packing		Weight lb
			Inner	Master	
1/8	36X 1001L	0.54	20	320	0.1
1/4	36X 1002L	0.71	40	320	0.2
3/8	36X 1003L	0.82	40	160	0.1
1/2	36X 1004L	1.01	30	120	0.4
3/4	36X 1006L	1.18	20	80	0.7
1	36X 1010L	1.43	20	40	1.0
1-1/4	36X 1012L	1.69	-	20	1.6
1-1/2	36X 1014L	1.84	-	18	2.1
2	36X 1020L	2.12	-	10	3.2
2-1/2	36X 1024L	2.70	-	6	5.5
3	36X 1030L	3.08	-	4	8.2

Fig. 36C 1L – Cap



Size in	Part Number	A in	Packing		Weight lb
			Inner	Master	
1/8	36C 1001L	0.53	120	1920	0.03
1/4	36C 1002L	0.63	80	1280	0.06
3/8	36C 1003L	0.68	60	720	0.1
1/2	36C 1004L	0.80	75	600	0.1
3/4	36C 1006L	0.90	40	320	0.1
1	36C 1010L	1.08	25	200	0.3
1-1/4	36C 1012L	1.12	25	100	0.5
1-1/2	36C 1014L	1.17	25	100	0.6
2	36C 1020L	1.36	18	72	0.9
2-1/2	36C 1024L	1.70	20	40	1.9
3	36C 1030L	1.80	12	24	2.7
4	36C 1040L	2.08	6	12	4.4

Fig. 36SC1L – Square Head Cored Plug



Size in	Part Number	A in	Packing		Weight lb
			Inner	Master	
1/2	36SC1004L	1.00	50	800	0.1
3/4	36SC1006L	1.15	30	360	0.1
1	36SC1010L	1.30	20	240	0.2
1-1/4	36SC1012L	1.40	40	160	0.3
1-1/2	36SC1014L	1.50	30	120	0.5
2	36SC1020L	1.60	20	80	0.7
2-1/2	36SC1024L	1.85	16	64	1.0
3	36SC1030L	1.95	16	32	2.0
4	36SC1040L	2.30	8	16	3.6

Fig. 36SS1L – Square Head Solid Plug



Size in	Part Number	A in	Packing		Weight lb
			Inner	Master	
1/8	36SS1001L	0.65	300	4800	0.02
1/4	36SS1002L	0.75	150	2400	0.03
3/8	36SS1003L	0.85	100	1600	0.06
1/2	36SS1004L	1.00	50	800	0.1
3/4	36SS1006L	1.15	30	360	0.1
1	36SS1010L	1.30	20	240	0.3
1-1/4	36SS1012L	1.40	40	160	0.6
1-1/2	36SS1014L	1.50	30	120	0.8
2	36SS1020L	1.60	20	80	1.2