SPECIAL NIPPLES

STAINLESS STEEL NIPPLES

Size	Length of Close	Close	1-1/2	2	2-1/2	3	3-1/2	4	4-1/2	5	5-1/2	6	7	8	9	10	11	12
1/8”	3/4	1	3	4	5	6	7	8	9	10	12	13	15	17	19	21	24	26
1/4”	7/8	2	5	7	9	11	13	14	14	16	18	20	22	26	33	37	41	44
3/8”	1	4	6	9	12	14	16	19	21	24	27	29	34	39	44	48	53	58
1/2”	1-1/8	6	8	12	15	18	22	26	30	33	36	39	46	53	61	68	75	82
3/4”	1-3/8	10	12	15	20	25	30	35	40	45	50	56	66	76	86	95	105	115
1”	1-1/2	15		21	28	36	43	52	58	65	71	77	91	105	118	132	146	160
1-1/4”	1-5/8	23		30	41	52	59	66	75	84	94	105	125	146	166	187	207	227
1-1/2”	1-3/4	32		38	48	60	70	83	94	105	118	131	155	180	204	228	252	277
2”	2	50			75	90	103	118	134	150	165	180	212	244	276	308	340	372
2-1/2”	2-1/2	90				115	140	165	190	215	240	260	310	360	410	460	510	560
3”	2-5/8	135				170	205	240	280	315	350	385	455	525	595	665	735	805
3-1/2”		200						330	390	425	455	490	580	670	760	850	935	1025
4”	2-7/8	230						360	410	455	505	550	645	740	835	930	1025	1120

STANDARDS AND SPECIFICATIONS

All stainless steel nipples that are domestically produced or imported are made to the highest quality in compliance to the ASTM A733 standard.
Stainless steel nipples are manufactured from either welded or seamless pipes in accordance to ASTM A312/A312M.

Standard nipple threads are NPT National (American) Pipe Taper Threads in accordance to ASME B.1.20.1.
In addition to the standard NPT threads, nipples are available in a variety of thread forms. See NPT Thread Data.

(800) 257-9559
Fax: (866) 706-5260
sales@trentonpipe.com