TUBING CUTTERS AND JACKET STRIPPING TOOL:

APPLICATION:

- Tubing Cutters, fitted with cutting wheel designed to cut stainless steel, create clean cuts for optimal flaring of tubing.
- Jacket Stripping Tool for cutting and removal of outer CSST jackets & metal shield before connecting fitting. Allows for clean, quick and proper fitting assembly.

MATERIAL / SPECIFICATIONS:

- Aluminum alloy body.
- Jacket Stripping Tool — durable plastic body and stainless steel blade.

Tubing Cutters

Jacket Stripping Tool

TUBING CUTTERS

Part No.	Description	Pkg. Qty.	Lbs./Ea.
GTCUTTER-SM2	Cutter with flat rollers – ⅜" – 1" FlashShield+™ CSST	1 Ea.	1.5
GTCUTTER-LG2	Cutter with flat rollers – Up to 2" FlashShield+™ CSST	1 Ea.	2.1
GTBLADE-SM-5	Replacement blade for GTCUTTER-SM2 (19 mm diam.)	5 Ea.	0.3
GTBLADE-LG2-5	Replacement blade for GTCUTTER-LG2 (30 mm diam.)	5 Ea.	0.4

JACKET STRIPPING TOOL

Part No.	Description	Pkg. Qty.	Lbs./Ea.
STRP4-8-11-24	½" + ¾" Jacket Stripping Tool	24 Ea.	3
STRP4-16-20-24	1" + 1-¼" Jacket Stripping Tool	24 Ea.	4.3

REGULATORS:

APPLICATION:

- For use in elevated pressure systems (in excess of ½ PSI) to reduce pressure to standard appliance use levels.
- Outdoor vent protector is used when vent-limiting orifice is removed for outdoor installation of regulator.

MATERIAL / SPECIFICATIONS:

- 2 PSI inlet pressure line models available in 8"WC and 11"WC outlet pressures.
- 5 PSI inlet pressure (OPD) models available in 8"WC (field adjustment to 11"WC) outlet pressures.

Maxitrol Regulators

Maxitrol Regulators with OPD

OARA Regulators

Pietro Fiorentini Regulators

LINE REGULATORS - NATURAL GAS, 8" W.C. OUTLET SETPOINT

MAXITROL REGULATORS

Part No.	Regulator Application	NPT	Capacity*(CFH)	Pkg. Qty	Wt. (Lbs.)
T325-3-44	2 PSI	½"	258	1	0.8
T325-5-2	2 PSI	½"	516	1	1.8
T325-5-44	2 PSI	¾"	620	1	1.8
T325-5-3	2 PSI	1"	620	1	1.8
T325-7AL-NG01	2 PSI	1-¼"	1,291	1	3.5

MAXITROL O.P.D.'S

T325-3L48	5 PSI	½"	207	1	1.5
T325-5AL600	5 PSI	¾"	439	1	3.4
T325-7L-210D**	5 PSI	1-¼"	1,291	1	9.2

OARA REGULATORS

REG8-300	2 PSI	½"	238	1	0.8
REG8-600	2 PSI	¾"	462	1	1.9

PIETRO FIORENTINI REGULATORS

30051-NG	2 PSI	½"	552	1	1.7
30052-NG	2 PSI	¾"	665	1	1.7
30053-NG	2 PSI	1"	893	1	1.6
30153-NG	2 PSI	1-¼"	3,735	1	7.4

*Natural gas, 0.60 specific gravity. 1 PSI inlet, 8" w.c. outlet
See Gastite®/FlashShield+™ Design & Installation Guide, table 4-7 for further sizing info.

**Vent limiter not available for -7 OPD