Madera™ FloWise® 15" Height Elongated Flushometer Toilet

VITREOUS CHINA LESS EVERCLEAN®

Madera™ FloWise® 15" Height Elongated LESS EverClean®

- Floor mount flushometer valve toilet
- Vitreous china
- High Efficiency, Low Consumption. Operates in the range of 1.1 gpf to 1.6 gpf (4.2 Lpf to 6.0 Lpf)
- Meets definition of HET (High Efficiency Toilet) when used with a high efficiency flush valve (1.28 gpf or 1.6 / 1.1 gpf dual flush)
- Fully glazed 2-1/8" trapway
- Elongated bowl
- 10" or 12" roughing-in
- 15" rim height
- Condensation channel
- Powerful direct-fed siphon jet action
- 10" x 12" water surface area
- 1-1/2" inlet spud
- 2 bolt caps

❏ **2234.001** Elongated bowl only, top spud
❏ **2623.001** Elongated bowl only, top spud with slotted rim for bedpan holding
❏ **2624.001** Elongated bowl only, back spud

System MaP* Score:
- 1,000 grams of miso @ 1.1 gpf, 1.28 gpf or 1.6 gpf when used with an American Standard flush valve

* Maximum Performance (MaP) testing performed by IAPMO R&T Lab. MaP Report conducted by Veritec Consulting, Inc. and Koeller and Company.

Component Parts:
❏ **047007-0070A** Inlet Spud (furnished with bowl)
❏ **481310-100** Bolt caps with retainers (furnished with bowl)

Nominal Dimensions:
718 x 356 x 381mm
(28-1/4" x 14" x 15")

Fixture only, less seat and flush valve

Recommended working pressure–between 25 psi at valve when flushing and 80 psi static

Compliance Certifications - Meets or Exceeds the Following Specifications:
- ASME A112.19.2 / CSA B45.1 for Vitreous China Fixtures

SEE REVERSE FOR ROUGHING-IN DIMENSIONS

To Be Specified:
❏ Color: ❏ White
❏ Seat:
- ❏ American Standard #5901.100 Heavy duty open front less cover
- ❏ American Standard #5905.100 Extra heavy duty open front less cover

❏ Flushometer Valve:
- ❏ 1.6 gpf:
  - ❏ Sensor-Operated: American Standard Selectronic® DC Power #6065.161.002 (Top Spud)
  - ❏ Sensor-Operated: American Standard Selectronic® AC Power #6067.261.002 (Back Spud)
  - ❏ Manual: American Standard #6047.161.002 (Top Spud)
- ❏ 1.28 gpf:
  - ❏ Sensor-Operated: American Standard Selectronic® DC Power #6065.121.002 (Top Spud)
  - ❏ Sensor-Operated: American Standard Selectronic® AC Power #6067.221.002 (Back Spud)
  - ❏ Manual: American Standard #6047.121.002 (Top Spud)
- ❏ 1.6 / 1.1 gpf Dual Flush:
  - ❏ Sensor-Operated: American Standard Selectronic® DC Power #6065.761.002 (Top Spud)

ENVIROMENTAL PRODUCT DECLARATION

When used with **1.1 or 1.28 gpf** toilet flush valves

WATER EFFICIENT

© 2018 AS America Inc.

Madera™ FloWise® 15" Height Elongated Flushometer Toilet

VITREOUS CHINA LESS EVERCLEAN®

2234.001/2623.001



2624.001



NOTES:
PRODUCT 2234 SHOWN, 2623 SAME EXCEPT WITH SLOTTED RIM FOR BED PAN HOLDING.
TO COMPLY WITH AREA CODE GOVERNING THE HEIGHT OF VACUUM BREAKER ON THE FLUSHOMETER VALVE, THE PLUMBER MUST VERIFY DIMENSIONS SHOWN FOR SUPPLY ROUGHING.
THIS TOILET DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 254MM (10") AND A MAXIMUM DIMENSION OF 305MM (12") FROM FINISHED WALL TO C/L OF OUTLET.
FLUSHOMETER VALVE NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY. FLUSHOMETER VALVE REQUIREMENTS FOR 12" (305MM) ROUGH-IN: SWEAT EXTENSION NIPPLE IS REQUIRED. REFER TO VALVE MANUFACTURER AND LOCAL CODES.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

© 2018 AS America Inc.

PART OF LIXIL