

Spring-Clamp Connection Terminal Blocks

Standard Feed-Through Blocks

	1492-L6				1492-L6T				1492-L10					
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.														
Specifications	Feed-through terminal block				Feed-through terminal block with 2 connection points on one side				Feed-through terminal block					
Certifications		CSA	IEC	ATEX		CSA	IEC	ATEX		CSA	IEC	ATEX		
Voltage Rating	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC		
Maximum Current	50 A		41 A	36 A	50 A		41 A	36 A	60 A	55 A	57 A	50 A		
Wire Range (Rated Cross Section)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (20...8 AWG)	#22...8 AWG	#20...8 AWG	6 mm ²	6 mm ² (#20...10 AWG)	#16...6 AWG		10 mm ²	10 mm ² (16...8 AWG)		
Wire Strip Length	0.51 in. (13 mm)				0.51 in. (13 mm)				0.70 in. (18 mm)					
Density	37 pcs/ft (123 pcs/m)				37 pcs/ft(123 pcs/m)				30 pcs/ft (99 pcs/m)					
Housing Temperature Range	-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)					
Short-Circuit Current Rating	See page 12-78													
Terminal Blocks	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.					
Color	Grey	1492-L6	50	1492-L6T	50	1492-L10	25	Red	1492-L6-RE	50	1492-L6T-RE	50	1492-L10-RE	25
	Blue	1492-L6-B	50	1492-L6T-B	50	1492-L10-B	25	Black	1492-L6-BL	50	1492-L6T-BL	50	1492-L10-BL	25
	Green	1492-L6-G	50	1492-L6T-G	50	1492-L10-G	25	Yellow	1492-L6-Y	50	1492-L6T-Y	50	1492-L10-Y	25
	Orange	1492-L6-OR	50	1492-L6T-OR	50	1492-L10-OR	25	Brown	1492-L6-BR	50	1492-L6T-BR	50	1492-L10-BR	25
	White	1492-L6-W	50	1492-L6T-W	50	1492-L10-W	25							
Accessories	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.	Cat. No.		Pkg Qty.					
Mounting Rails	199-DR1		10	199-DR1		10	199-DR1		10					
1 m Symmetrical DIN (Steel)	1492-DR5		10	1492-DR5		10	1492-DR5		10					
1 m Symmetrical DIN (Aluminum)	1492-DR6		2	1492-DR6		2	1492-DR6		2					
1 m Hi-Rise Sym. DIN (Aluminum)	1492-DR7		2	1492-DR7		2	1492-DR7		2					
1 m Angled Hi-Rise Sym. DIN (Steel)	Grey	1492-EBL6	50	1492-EBL6T	50	1492-EBL10	20	Blue	1492-EBL6-B	50	1492-EBL6T-B	50	1492-EBL10-B	20
End Barriers	Yellow	1492-EBL6-Y	50	1492-EBL6T-Y	50	1492-EBL10-Y	20							
End Anchors and Retainers	1492-ERL35		20	1492-ERL35		20	1492-ERL35		20					
Screwless End Retainer	1492-EAJ35		100	1492-EAJ35		100	1492-EAJ35		100					
DIN Rail — Normal Duty	1492-EAHJ35		50	1492-EAHJ35		50	1492-EAHJ35		50					
DIN Rail — Heavy Duty	1492-CJL8-32		10	1492-CJL8-32		10	—		—					
Jumpers	1492-CJL8-4		60	1492-CJL8-4		60	—		—					
Plug-in Center Jumper — 4-Pole	1492-CJL8-3		60	1492-CJL8-3		60	—		—					
Plug-in Center Jumper — 3-Pole	1492-CJL8-2		60	1492-CJL8-2		60	1492-CJL10-2		25					
Plug-in Center Jumper — 2-Pole	—		—	—		—	1492-TP23		20					
Other Accessories	1492-TPL8		25	1492-TPL8		25	—		—					
Test Plug (Stackable)	1492-EWPL8		20	1492-EWPL8		20	1492-EWPL10		20					
Electrical Warning Plate	1492-M6X12 (120/card)		5	1492-M6X12 (120/card)		5	1492-M6X12 (120/card)		5					
Marking Systems	1492-MR8X12 (84/card)		5	1492-M8X5 (160/card)		5	1492-M8X5 (160/card)		5					
Snap-In Marker Cards*	1492-MH6X12 (80/card)		5	1492-MH6X12 (80/card)		5	1492-MH5X15 (96/card)		5					
Hinged Marker Cards	—		—	—		—	—		—					

* May only be mounted in terminal block corner marking positions.