

Spring-Clamp Connection Terminal Blocks

Multi-Circuit Feed-Through Blocks

	1492-LD2			1492-LD3				1492-L3QS			
Dimensions are not intended to be used for manufacturing purposes. Note: Height dimension is measured from top of rail to top of terminal block.											
Specifications	<i>Two-circuit feed-through terminal block</i>			<i>Two-circuit feed-through terminal block</i>				<i>Side-by-side Two circuit Terminal Block</i>			
Certifications		CSA	IEC		CSA	IEC	ATEX		CSA	IEC	ATEX
Voltage Rating	300V AC/DC	600V AC/DC	500V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC	600V AC/DC		800V AC/DC	550V AC/DC
Maximum Current	10 A		17.5 A	20 A	25 A	24 A	20 A	25 A	27 A	24 A	21 A
Wire Range (Rated Cross Section)	#28... 16 AWG		1.5 mm ²	#30... 12 AWG		2.5 mm ²	0.5... 2.5 mm ² (#20...14 AWG)	#26... 12 AWG		2.5 mm ²	2.5 mm ² (20... 12 AWG)
Wire Strip Length	0.39 in. (10 mm)			0.39 in. (10 mm)				0.39 in. (10 mm)			
Density	87 pcs/ft (285 pcs/m)			59 pcs/ft (196 pcs/m)				59 pcs/ft (196 pcs/m)			
Housing Temperature Range	-58...+248 °F (-50...+120 °C)			-58...+248 °F (-50...+120 °C)				-58...+248 °F (-50...+120 °C)			
Terminal Blocks	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.			
Color	Grey	1492-LD2	50	1492-LD3	25	1492-L3QS	50				
	Red	1492-LD2-RE	50	1492-LD3-RE	25	1492-L3QS-RE	50				
	Blue	1492-LD2-B	50	1492-LD3-B	25	1492-L3QS-B	50				
	Black	1492-LD2-BL	50	1492-LD3-BL	25	1492-L3QS-BL	50				
	Green	1492-LD2-G	50	1492-LD3-G	25	1492-L3QS-G	50				
	Yellow	1492-LD2-Y	50	1492-LD3-Y	25	1492-L3QS-Y	50				
	Orange	1492-LD2-OR	50	1492-LD3-OR	25	1492-L3QS-OR	50				
	Brown	1492-LD2-BR	50	1492-LD3-BR	25	1492-L3QS-BR	50				
	White	1492-LD2-W	50	1492-LD3-W	25	1492-L3QS-W	50				
Accessories	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.	Cat. No.	Pkg Qty.			
Mounting Rails											
1 m Symmetrical DIN (Steel)	199-DR1	10	199-DR1	10	199-DR1	10					
1 m Symmetrical DIN (Aluminum)	1492-DR5	10	1492-DR5	10	1492-DR5	10					
1 m Hi-Rise Symmetrical DIN (Aluminum)	1492-DR6	2	1492-DR6	2	1492-DR6	2					
1 m Angled Hi-Rise Sym. DIN (Steel)	1492-DR7	2	1492-DR7	2	1492-DR7	2					
End Barriers	Grey	1492-EBLD2	50	1492-EBLD3	20	1492-EBL3Q	50				
	Blue	1492-EBLD2-B	20	1492-EBLD3-B	20	1492-EBL3Q-B	50				
	Yellow	1492-EBLD2-Y	20	1492-EBLD3-Y	20	1492-EBL3Q-Y	50				
End Anchors and Retainers											
Screwless End Retainer	1492-ERL35	20	1492-ERL35	20	1492-ERL35	20					
DIN Rail — Normal Duty	1492-EAJ35	100	1492-EAJ35	100	1492-EAJ35	100					
DIN Rail — Heavy Duty	1492-EAHJ35	50	1492-EAHJ35	50	1492-EAHJ35	50					
Jumpers											
Plug-in Center Jumper — 50-Pole	—	—	1492-CJK5-50	10	—	—					
Plug-in Center Jumper — 10-Pole	1492-CJL4-10	20	1492-CJK5-10	20	—	—					
Plug-in Center Jumper — 9-Pole	—	—	1492-CJK5-9	20	—	—					
Plug-in Center Jumper — 8-Pole	—	—	1492-CJK5-8	20	—	—					
Plug-in Center Jumper — 7-Pole	—	—	1492-CJK5-7	20	—	—					
Plug-in Center Jumper — 6-Pole	—	—	1492-CJK5-6	20	—	—					
Plug-in Center Jumper — 5-Pole	1492-CJL4-5	60	1492-CJK5-5	20	—	—					
Plug-in Center Jumper — 4-Pole	1492-CJL4-4	60	1492-CJK5-4	60	—	—					
Plug-in Center Jumper — 3-Pole	1492-CJL4-3	60	1492-CJK5-3	60	—	—					
Plug-in Center Jumper — 2-Pole	1492-CJL4-2	60	1492-CJK5-2	60	—	—					
Other Accessories											
Reducing Sleeves #28...24 AWG (0.13...0.2 mm ²)	1492-PSL2-2	100	1492-PSLS2-2	100	1492-PSL3-2	100					
Reducing Sleeves #22...20 AWG (0.25...0.5 mm ²)	1492-PSL2-5	100	1492-PSLS2-5	100	1492-PSL3-5	100					
Reducing Sleeves #18 AWG (0.75...1.0 mm ²)	—	—	—	—	1492-PSL3-10	100					
Test Plug	1492-TPL4	25	—	—	1492-TP23	20					
					1492-TPL5	25					
Electrical Warning Plate	1492-EWPL4	20	—	—	1492-EWPL5	20					
Group Marking Carrier	1492-GM35	25	1492-GM35	25	1492-GM35	25					
Marking Systems											
Snap-In Marker Cards	1492-M3X12 (120/card)*	5	1492-M5X10 (144/card)	5	1492-M5X10 (144/card)	5					
	1492-M3X5 (100/card)	5	1492-M5X5 (200/card)	5	1492-M5X5 (200/card)	5					
Hinged Marker Cards	—	—	—	—	1492-MH5X10 (96/card)	5					

* May only be mounted in terminal block corner marking positions.