

FiberRunner® Accessories



FR38DR



FR716DR



FR516DR



FRUIB-X



FRSSM2



FRSTRCLIP



FRTBKT-X

Part Number	Part Description	For Threaded Rod Size	Std. Pkg. Qty.	Std. Ctn. Qty.
3/8" Nut Driver				
FR38DR	Used to disassemble 4x4, 6x4, and 12x4 FiberRunner® QuikLock™ Couplers when required.	—	1	10
7/16" Nut Driver				
FR716DR	7/16" nut driver for use with the FiberRunner®, GridRunner™, and Wyr-Grid™ Systems.	—	1	10
5/16" Nut Driver				
FR516DR	Used to disassemble 2x2 FiberRunner® QuikLock™ Couplers when required.	—	1	10
Universal Innerduct Bracket				
FRUIB-X	Used to secure any size corrugated tubing or innerduct to any surface including equipment racks and channel or fittings. Two 1/4" (6.3mm) holes must be drilled through to secure brackets.	—	10	100
Slack Spool Manager with 2.37" Bend Radius Diameter				
FRSSM2	The slack spool manager can be mounted in 12x4, 6x4, and 4x4 FiberRunner® Channels and in 4x4 Fiber-Duct™ Channel to create an in-channel slack management. It can be deployed in a vertical or horizontal channel run and can withstand a 20 lb. load without pulling away from the base. Mounting fasteners are included.	—	1	5
Strut Clip Kit				
FRSTRCLIP	Strut mounting clip assembly allows FiberRunner® Channel to be attached directly to standard 1 5/8" wide strut structures. Contains two clips and all hardware for assembly. Bolts release with 7/16" nut driver.	—	1	10
1/4" T-Bolt Kit				
FRTBKT-X	T-bolts can be used for additional attachment when securing FiberRunner® Channel to mounting brackets. For example, a T-bolt can be inserted thru a 12x4 mounting bracket and positioned within the center rib structure on the underside of 12x4 channel. By tightening the nut, the 12x4 channel is more securely fastened to the mounting bracket.	—	10	100

Table continued on next page

FiberRunner® Accessories (continued)



FRQMC-X

TR1-12-X
TR1-58-X

TRC18FR-X8Y



CLT150F-X3

Part Number	Part Description	For Threaded Rod Size	Std. Pkg. Qty.	Std. Ctn. Qty.
-------------	------------------	-----------------------	----------------	----------------

FiberRunner® Quick Mount Clips

FRQMC-X	Used wherever additional FiberRunner® Slide Clamps would be helpful. For example, use on 12x4 FiberRunner® QuikLock™ Brackets to accommodate dual runs of 6x4 or 4x4 FiberRunner® Channel.	—	10	100
----------------	--	---	----	-----

Threaded Rod in One Foot Lengths

TR1-12-X	Threaded rod can be used with various mounting brackets. Length = 12" (305mm).	1/2"	10	—
TR1-58-X	Threaded rod can be used with various mounting brackets. Length = 12" (305mm).	5/8"	10	—

Threaded Rod Cover

TRC18FR-X8Y	Used to protect cabling from threaded rod. Vertical slit allows easy installation. For indoor use only. Gray.	1/2" – 5/8"	10	100
--------------------	---	-------------	----	-----

Slit Corrugated Loom Tubing

CLT150F-X3*	Slit corrugated loom tubing provides a vertical pathway as cables transfer from the FiberRunner® Fitting to the equipment below. Inside diameter is 1.48" (37.6mm) and outside diameter 1.73" (43.9mm). Sold in 10' rolls.	—	1	—
--------------------	--	---	---	---

*For other colors replace suffix X3 (Orange) with X4 (Yellow) or X20 (Black).