




GridRunner™ Underfloor Cable Routing System




Cable Fills for GridRunner™ Underfloor Cable Routing System

"X"	"Y"	Internal Area In. ²	Category 6A (SD) Diameter 6.1mm 0.240"	Category 6A Diameter 7.6mm 0.300"	Category 6 Diameter 6.1mm 0.240"
			50% Fill	50% Fill	50% Fill
12.0	4.0	48.0	531	340	531
12.0	6.0	72.0	796	509	796
21.7	4.0	86.8	959	614	959
21.7	6.0	130.3	1440	922	1440


The above cable dimensions represent the nominal Panduit cable diameter per performance level. For specific cable fill information based on specific part numbers, please contact Panduit customer service.

GridRunner™ Wire Baskets

- Drop-in wire basket sections are supplied in two widths (21" and 12"), two depths (4" and 6"), and two lengths (24" and 48")
- Feature all rounded edges
- Require no cutting or deburring of sharp edges
- Accommodate 24" x 24" and 600mm x 600mm raised floor grids
- Made from pre-galvanized steel wire




GR21X6X24PG



GR21X6X48PG




GR21X4X24PG




GR21X4X48PG

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
21" Wide Wire Basket Sections			
GR21X6X24PG	21"W x 6"D x 24"L section used to carry cables horizontally throughout the system. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2
GR21X6X48PG	21"W x 6"D x 48"L section used to carry cables horizontally throughout the system. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2
GR21X4X24PG	21"W x 4"D x 24"L section used to carry cables horizontally throughout the system. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2
GR21X4X48PG	21"W x 4"D x 48"L section used to carry cables horizontally throughout the system. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2

GridRunner™ Wire Baskets (continued)



GR12X6X24PG




GR12X6X48PG




GR12X4X24PG



GR12X4X48PG




GR12X6X24OSPG



GR12X6X48OSPG



GR12X4X24OSPG



GR12X4X48OSPG

Part Number	Part Description	Std. Pkg. Qty.	Std. Ctn. Qty.
12" Wide Wire Basket Sections			
GR12X6X24PG	12"W x 6"D x 4"L section used to carry cables horizontally throughout the system. Centers the basket between pedestal supports. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2
GR12X6X48PG	12"W x 6"D x 48"L section used to carry cables horizontally throughout the system. Centers the basket between pedestal supports. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2
GR12X4X24PG	12"W x 4"D x 24"L section used to carry cables horizontally throughout the system. Centers the basket between pedestal supports. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2
GR12X4X48PG	12"W x 4"D x 48"L section used to carry cables horizontally throughout the system. Centers the basket between pedestal supports. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2
12" Wide Offset Wire Basket Sections			
GR12X6X24OSPG	12"W x 6"D x 24"L section used to carry cables horizontally throughout the system. Offsets 12" basket towards one side. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2
GR12X6X48OSPG	12"W x 6"D x 48"L section used to carry cables horizontally throughout the system. Offsets 12" basket towards one side. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2
GR12X4X24OSPG	12"W x 4"D x 24"L section used to carry cables horizontally throughout the system. Offsets 12" basket towards one side. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2
GR12X4X48OSPG	12"W x 4"D x 48"L section used to carry cables horizontally throughout the system. Offsets 12" basket towards one side. Attaches to GRPBPG pedestal bracket to provide secure connection and electrical bond to raised floor pedestal.	—	2