



Representative

Catalog Number: 162LR-B-5220
Product ID: 7TAA121100R0182
UPC Number: 07511418641
Status: Active

15kV 200 Amp, Loadbreak Elbow Connector with Test Point, .635 inch - .905 inch Cable Insulation Diameter, #2 Stranded Wire Size. Bi-Metal Compression Lug

North American Specifications (UNSPSC)

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Elastimold
Type	Loadbreak Elbow Connector with Test Point
Special Features	Fully Shielded, Fully Submersible Molded Rubber Housing, 100 Percent Peroxide-Cured Construction includes Insulation and Conductive EPDM Materials. Provision for Hot Stick Operation. Provision for Ground Wire Connection. Non-Corrosive Capacitive Test Point.
Application	The 162LR is designed for Connecting to and Operating 15kV Class, 200 Amp Distribution apparatus. It Provides a Convenient Method to Connect/ Disconnect Cable and Equipment on Power Distribution Systems.
Standard	ANSI/IEEE Standard 386
Conductor Range	#2 Stranded Wire Size.
Material	Housing - EPDM Rubber
Color	Black
Voltage Rating	15kV
Amperage Rating	200 Amps
Insulation	Yes, EPDM Rubber
Temperature Rating	-20 Degrees C to +65 Degrees C
Environmental Conditions	Products are designed and constructed for all applications including Padmount, Subsurface, Vault, Indoor, Outdoor, Direct Sunlight, Direct Buried and Continuously Submerged in Water.
Consist Of	(1) Elbow Connector Housing, (1) Bi-Metal Compression Lug, (1) Probe, (1) Probe Wrench, (1) Lubricant Tube, (1) Crimp Chart, (1) V.D. Cap-Peroxide, (1) Installation Instructions

Packaging

Inner Quantity	1
Outer Quantity	15
Outer Dimensions (inches)	10.5x19.12x12.5
Weight Uom	2.12 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet	Available on Website
Instruction Sheet	Available on Website
Support/Tools	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
 www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email:techsupport@tnb.com