



Representative

**Catalog Number:** NCG-M122LG  
**Product ID:** 7TCA303070R0078  
**UPC Number:** 78621015236  
**EAN Number:** 05415022424164  
**Status:** Active

Non Armoured Cable Gland, Thread Size M12, Cable Range 3 to 6.5 Millimeters, Thread Length 8 Millimeters, Nylon, Light Grey

- Low profile compact cable glands
- Wide cable clamping range
- Good corrosion resistance

#### North American Specifications (UNSPSC)

|                    |                                                             |
|--------------------|-------------------------------------------------------------|
| UNSPSC             | 39121431 Cable gland connector                              |
| IGCC               | 4601 Cable gland connector                                  |
| Brand Name         | T&B                                                         |
| Type               | Non Armoured Cable Gland                                    |
| Application        | General purpose, Panel building, Light fixture and housings |
| Standard           | UL514B, CSA, RoHS, WEEE, LVD                                |
| Size               | M12                                                         |
| Conductor Range    | 3 to 6.5 Millimeters                                        |
| Material           | Nylon                                                       |
| Color              | Light Gray                                                  |
| NEMA Rating        | NEMA 4                                                      |
| Temperature Rating | -20 to +100 Degrees C                                       |

#### European Specifications (ETIM)

|                               |                            |
|-------------------------------|----------------------------|
| ETIM                          | EC000441 Cable screw gland |
| Thread type                   | Metric                     |
| Nominal thread size metric/PG | 12                         |
| Pitch thread                  | 1.5mm                      |
| Thread length                 | 8mm                        |
| Suitable for cable diameter   | 3 - 6.5mm                  |
| Material                      | Plastic                    |
| Material quality              | Polyamide (PA)             |
| Halogen free                  | Y                          |
| Degree of protection (IP)     | IP68                       |
| Colour                        | Light grey                 |
| Model                         | Straight                   |
| Operating temperature         | -20-+100°C                 |

#### Packaging

|                           |                  |
|---------------------------|------------------|
| Inner Quantity            | 10               |
| Inner Dimensions (inches) | 7.09x3.54x3.54   |
| Outer Quantity            | 100              |
| Outer Dimensions (inches) | 3.94x15.75x11.02 |
| Weight Uom                | 0.01 lbs. Each   |

#### Documents / Support Tools

|                                       |                      |
|---------------------------------------|----------------------|
| Technical Drawing / Data Sheet        | TDS000030            |
| Technical Drawing / Data Sheet Canada | TDS000030            |
| Instruction Sheet                     | TA05283-TB2          |
| Support/Tools                         | Available on Website |
| Video US                              | Available on Website |

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)