

Thomas&Betts

Actual



Representative

Catalog Number: Product ID: UPC Number: Status:

2688 7TAD105050R0005 78621002688 Active

Liquidtight Cord Connector, 1 Inch, 90 Degree Bend, Cord Range 0.560 to 0.690 Inch, Meets Coast Guard CG293, Nylon, Black

- Segmented chuck provides high mechanical pullout performance, will not cut or damage cord jacket.
- Temperature Rating: -34 to +105 Degrees Celsius
- Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC. Class I, Div 2; Class II, Div 1 & amp; 2; Class III, Div 1 & amp; 2; NEC 501-4(b), 502-4(a)(b), 503-3(a)(b)
- Meets Coast Guard CG293

North American Specifications (UNSPSC)

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	T&B
Туре	Cord Connectors-90 Degree
Special Features	Hand Tightens, No Tools Needed for Assembly
Application	To Connect Flexible Cord to a Box or Enclosure
	and Provide Adequate Strain Relief.
Standard	UL E13938, CSA
Size	1 Inch
Conductor Range	0.560 to 0.690 Inch
Material	Nylon
Color	Black
Temperature Rating	-34 to +105 Degrees C

European Specifications (ETIM)

ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	1 inch
Thread length	19.56mm
Suitable for cable diameter	14.224-17.526mm
Material	Plastic
Material quality	Polyamide (PA)
Colour	Black
Model	90°-elbow
Operating temperature	-34-+105°C
Packaging	
Inner Quantity	5
Inner Dimensions (inches)	6x5x4
Outer Quantity	25
Outer Dimensions (inches)	13x10.6x5.6
Weight Uom	20 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet	TA01320-TB2

Header

3D Model

Available on Website



Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com