



Actual

Catalog Number: 035-72775-12
Product ID: 7TBD012980R0004
UPC Number: 78621063120
Status: Active

3/4 Inch Insulated Watertight Strain Relief Connector, Straight, Cable Size 0.625 to 0.750 Inch, Steel, Zinc Plated

North American Specifications (UNSPSC)

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	T&B
Type	Strain Relief Cord Connectors-Straight
Application	Provide Means for Passing a Cord Cable, Armored or Unarmored, Into an Enclosure, Through a Bulk-head or Into a Rigid Conduit
Size	0.625 to 0.750 Inch
Connection	Straight
Material	Steel

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	3/4 inch
Model	Straight
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	NPT
Thread connection size	None
Material housing	Steel
Surface protection	Zinc coated

Packaging

Inner Quantity	10
Outer Quantity	100
Weight Uom	1 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com