

Representative

Catalog Number: 321-TB

 Product ID:
 7TAA106020R0013

 UPC Number:
 78621000321

Status: Active

Metal-Clad and Armored Cable Fitting, 90 Degree Bend, Trade Size 3/8 Inch, Knockout Size 1/2 Inch, Cable Range 0.470 to 0.660 Inch, Malleable Iron with Zinc Plating

- Throat is long enough to install in cast housing knockouts.
- To connect and effectively bond armored cable or flexible metal conduit to a box or an enclosure.

North American Specifications (UNSPSC)	
UNSPSC	39121419 Flex connectors
IGCC	4573 Flex connectors
Brand Name	T&B
Туре	Armored Cable/Flexible Metal Conduit Fittings
Special Features	The Angle Clip Gives Secure Mechanical Grip that
	Tightens Under Tension or Vibration
Application	For Use with Armored Cable and Flexible Metal
	Conduit
Standard	UL E23018, CSA 2884
Size	3/8 Inch
Connection	90 Degree
Conductor Range	0.470 to 0.660 Inch
Material	Steel
Finish	Electro Zinc Plated
Color	Metallic

European Specifications (ETIM)	
ETIM	EC001180 Screw connection for protective metallic
	hose
Nominal size in inch	3/8 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to	Other
housing	
Material housing	Other
Surface protection	Zinc coated
Thread length	9.525mm
Packaging	
Inner Quantity	50
Inner Dimensions (inches)	4.9x3.8x7.7
Outer Quantity	100
Outer Dimensions (inches)	8.3x5.3x8.3
Weight Uom	12.5 lbs. per 100

Hours: 7AM - 6PM CDT

Monday-Friday

## **Documents / Support Tools**

Technical Drawing / Data Sheet US Available on Website

## Header

3D Model Available on Website

For further technical assistance, please contact us...



Memphis, TN 38120 www.tnb.com

860 Ridge Lake Blvd. Memphis, TN 38120 Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com