

Actual

Catalog Number: LT75

 Product ID:
 7TAD012910R0028

 UPC Number:
 03448115202

Status: Active

3/4 Inch Black Liquidtight Non-metallic Omni Connector

- All nylon construction resists sale water, weak acids, gasoline, alcohol, oil, grease and common solvents.
- No threading of the conduit or tubing required to install.
- Complete conduit/connector system is reusable.
- · Lower installed cost.
- Black connectors provided with nylon locknut.
- Gray connectors provided with assembled O-ring and metal locknuts.

North American Specifications	(UNSPSC)
UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	Carlon
Туре	Liquidtight Fittings
Special Features	No Disassembly Required.
Application	Suitable for Indoor/outdoor Use.
Standard	UL E23018
Size	3/4 Inch
Material	Non-Metallic
Color	Black

European Specifications	(ETIM)
ETIM	EC001178 Screw connection for protective plastic
	hose
Nominal size in inch	3/4 inch
Degree of protection (IP)	IP68
Model	Straight
Revolving thread	N
Construction type	External thread
Type of connection	Plug-in connection
Thread connection size	Other
Thread length	15.9mm
One-piece	Υ
Material screw gland	Polyamide
Total length	51.60mm
Colour	Black

Packaging		
Inner Quantity	25	
Inner Dimensions (inches)	6.375x6.375x6.75	
Outer Quantity	200	
Outer Dimensions (inches)	14.25x14.25x14.75	
Weight Uom	0.09 lbs. Each	

Documents / Support Tools

Technical Drawing / Data Sheet WSD-AC03717

For further technical assistance, please contact us...



860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com

MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com