



Representative



Representative

Catalog Number: XPLFL115
Product ID: 7TAD013340R0002
UPC Number: 78620988430
Status: Active

1/2 Inch x 15 Inch XP Flex Explosion Proof Flexible Coupling

- UL Listed for use in hazardous and wet locations.
- Corrosion-resistant, ideal for washdown areas.
- Flexible bronze construction with arc-resistant inner sleeve and brass fittings.
- Terminated with two threaded female end fittings and male close nipples.
- No bonding jumper required.
- Flexible design allows for use to make tight bends or allow for movement or vibration.

North American Specifications (UNSPSC)

UNSPSC	39131707 Electrical conduit coupling
IGCC	5548 Electrical conduit coupling
Brand Name	T&B
Type	XP Flex Explosion-Proof Flexible Couplings-Hazardous Location
Special Features	No Bonding Jumper Required
Application	Explosion-Proof and Dust-Ignition-Proof for Use In Hazardous Locations
Standard	UL E193396, cULus
Trade Size	1/2 Inch
Length	15 in
Material	Brass
Connection	NPT Threads
Color	Metallic

European Specifications (ETIM)

ETIM	EC000939 Coupler for installation tubes
Material	Metal
Material quality	Other
Model	Thread
Two piece	N
With inspection opening and cover	N

Packaging

Outer Quantity	1
Outer Dimensions (inches)	15x2x2
Weight Uom	2.19 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000382
Technical Drawing / Data Sheet Canada	Available on Website

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com