



Family

Catalog Number: MD350F-4
Product ID: 7TAH007700R0024
UPC Number: 78620989324
Status: Active

KUBE Female Copper Motor Pigtail Disconnect, Wire Size 350 kcmil, Body Size 4, Die Color Code Red

- Fast, snap-together assembly offers maximum labor savings. Not need for nuts, bolts and washers or insulating tape - simply slide on reusable boot.
- Quick disconnect - no knife cutting of melted tape, eliminating the risk of accidental cutting of wire insulation, resulting motor downtime and installer exposure. Meets or exceeds electrical and mechanical performance of bolted connections.
- Female disconnects equipped with beryllium copper louvered contact bands for dependable connections.
- Application Tools: TBM6, TBM6S, TBM5, TBM5S, TBM8, TBM8S

North American Specifications (UNSPSC)

UNSPSC	39121447 Wire terminal disconnect
IGCC	4667 Wire terminal disconnect
Brand Name	Color-Keyed
Type	Motor Lead Disconnect
Special Features	Fast, snap-together assembly offers maximum labor savings. Not need for nuts, bolts and washers or insulating tape - simply slide on reusable boot.
Standard	UL E9809
Voltage Rating	600V
Material	Copper
Finish	Tin-Plated
Color	Red

Packaging

Inner Quantity	3
Inner Dimensions (inches)	3.5x3x3
Outer Quantity	15
Outer Dimensions (inches)	16.31x3.75x3.5
Weight Uom	51 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000392
Technical Drawing / Data Sheet Canada	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com