

Catalog Number: 266 1/2P
Product ID: 7TAA106070R0013
UPC Number: 78621094869
Status: Active

Squeeze Connector, 3/8 Inch, Armored Cable Squeeze Connector for 1/2 Inch, Knockout, 90 Degree Angle, For 3/8 Inch, Flexible Metal Conduit and Armored Cable 13/2, 14/3, 14/4, 12/2, 12/3, 12/4 and 10/2, Cable Opening .437 Inch, to .687 Inch, UL Listed for FEPMC and AC, Grounding Type, Special Thread Size.

North American Specifications (UNSPSC)

UNSPSC	39121419 Flex connectors
IGCC	4573 Flex connectors
Brand Name	T&B
Type	Armored Cable/Flexible Metal Conduit Fittings
Special Features	Cap Lifts off by Simply Loosening Screws Part Way, Only Two Screws to Tighten
Application	For Use with Armored Cable and Flexible Metal Conduit
Standard	CSA, UL
Size	3/8 Inch
Connection	90 Degree
Conductor Range	0.437 to 0.687 Inch
Material	Steel
Finish	Zinc Plated
Color	Metallic
Insulation	N

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	3/8 inch
Model	90°-elbow
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Other
Material housing	Other
Thread length	36.51mm
Approved in combination with protective conduit CSA	Y
Approved in combination with protective conduit UL	Y

Packaging

Inner Quantity	50
Inner Dimensions (inches)	8x5x4
Outer Quantity	100
Outer Dimensions (inches)	10.8x8.39x4.5
Weight Uom	13 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com