



Representative

Catalog Number: FPT4-1TL31-2C
Product ID: 7TAA003440R0003
UPC Number: 78599104285
Status: Active

Poke Through Base Unit, Length 19-3/4 Inches, Diameter 7-1/2 Inches, Hub Size 1/2 Inch, Galvanized Steel, 30A/125V Locking Receptacle, 2 Communications Receptacles

- Four modular configurations for power receptacles and communications jacks mounted flush with the floor
- Full access to communications compartment through the cover without exposing power compartments even after it is installed in the floor
- Threaded conduit hubs enable all communications cabling to be enclosed in a single conduit
- Accommodates fiber optic and audio/video connectors
- Pre-wired power receptacles

North American Specifications (UNSPSC)

UNSPSC	39121328 Fire rated poke through box
IGCC	4482 Fire rated poke through box
Brand Name	Steel City
Type	Poke Through Systems
Special Features	Four modular configurations for power receptacles and communications jacks mounted flush with the floor
Application	For above-grade, fire rated concrete floors.
Standard	UL E2969
Material	Die Cast Zinc/Galvanized Steel

European Specifications (ETIM)

ETIM	EC000024 Installation box for underfloor-installation
Cover model	Round
Suitable for wet cleaning	N
Suitable for hollow floor	Y
Material	Other
With opening carpeting	N
Colour	Other
Length external dimension	501.65mm
Outer diameter	190.5mm

Packaging

Outer Quantity	1
Outer Dimensions (inches)	21.38x8.13x5.5
Weight Uom	7.17 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000240
Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet	TA03724-TB2

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289

