# Thomas&Betts



Actual



Representative

### Catalog Number: Product ID: UPC Number: EAN Number: Status:

**2693** 7TAD105040R0010 78621002693 05414363140245 Active

Liquidtight Cord Connector, 3/4 Inch, Straight, Cord Range 0.250 to 0.400 Inch, Meets Coast Guard CG293, Nylon, Black

- Segmented chuck provides high mechanical pullout performance, will not cut or damage cord jacket.
- Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC. Class I, Div 2; Class II, Div 1 & amp; 2; Class III, Div 1 & amp; 2; NEC 501-4(b), 502-4(a)(b), 503-3(a)(b)
- Meets Coast Guard CG293

North American Specifications (UNSPSC)		
UNSPSC	39121431 Cable gland connector	
IGCC	4601 Cable gland connector	
Brand Name	T&B	
Туре	Cord Connectors-Straight	
Special Features	Hand Tightens, No Tools Needed for Assembly	
Application	To Connect Flexible Cord to a Box or Enclosure	
	and Provide Adequate Strain Relief.	
Standard	UL E13938, CSA	
Size	3/4 Inch	
Conductor Range	0.250 to 0.400 Inch	
Material	Nylon	
Color	Black	
Temperature Rating	-34 to +105 Degrees C	

# **European Specifications (ETIM)**

ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	3/4 inch
Thread length	15.875mm
Suitable for cable diameter	6.35-10.16mm
Material	Plastic
Material quality	Polyamide (PA)
Colour	Black
Model	Straight
Operating temperature	-34-+105°C

## Packaging

Inner Quantity	25
Inner Dimensions (inches)	8.2x5.2x4.4
Outer Quantity	100
Outer Dimensions (inches)	16.6x10.8x6.2
Weight Uom	6.5 lbs. per 100

#### **Documents / Support Tools**

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet	TA01320-TB2

#### Header

3D Model

Available on Website



Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com

#### For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com