



Actual



Representative

**Catalog Number:** 3303-C  
**Product ID:** 7TAA106100R0004  
**UPC Number:** 78621036089  
**Status:** Active

3/4 Inch Non-Metallic Sheathed Cable Two-Screw Connector, For Nonmetallic Sheathed Cables 8/2, 8/3 or 6/3, For Multiple (2) NM Cables 12/2 or 14/3, For Flexible Cords Cable Opening .530 Inch to .835 Inch, For Multiple Flexible Cords (2) 18/3 Minimum (.530 Combined Diameter Minimum), For Service Entrance Cable Minimum Opening .395 Inch X .622 Inch

## North American Specifications (UNSPSC)

UNSPSC	39121419 Flex connectors
IGCC	4573 Flex connectors
Brand Name	T&B Industrial Fitting
Sub Brand	CSA, UL E17583
Type	Nonmetallic Sheathed Cable Fittings
Application	To Connect Nonmetallic Sheathed Cable and Flexible Cord to a Box or an Enclosure.
Standard	CSA, UL
Size	3/4 Inch
Connection	Straight
Material	Steel - Non Insulated
Finish	Zinc Plated
Color	Metallic

## European Specifications (ETIM)

ETIM	EC001178 Screw connection for protective plastic hose
Nominal size in inch	3/4 inch
Model	Straight
Revolving thread	N
Construction type	External thread
Type of connection	Other
Thread connection size	Other

## Packaging

Inner Quantity	50
Inner Dimensions (inches)	4x5x8
Outer Quantity	250
Outer Dimensions (inches)	20.8x5.1x8.1
Weight Uom	10 lbs. per 100

## Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)