



Representative

**Catalog Number:** LT4100P-200  
**Product ID:** 7TAD012550R0007  
**UPC Number:** 78621090862  
**Status:** Active

1 Inch, 45 Degree Angle, for Type B FNMC Liquidtight Fitting and Flexible Non-metallic Conduit Meets Nema Ratings 4, 4X, 6, 6P, 12 and 13, Weather Stabilized Thermoplastic Material 200 Pieces.

#### North American Specifications (UNSPSC)

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	T&B
Type	Liquidtight Fittings
Application	T&B Bullet meets performance requirements when terminating Type B liquidtight non-metallic conduit or flexible non-metallic tubing to a box or enclosure with knockout opening or threaded hub.
Standard	UL E23018, CSA
Size	1 Inch
Connection	45 Degree
Material	Non-Metallic

#### European Specifications (ETIM)

ETIM	EC001178 Screw connection for protective plastic hose
Nominal size in inch	1 inch
Model	45°-elbow
Revolving thread	N
Construction type	External thread
Type of connection	Thread
Thread connection size	Other
Thread length	18.44mm
Material screw gland	Other
Material sealing	Other
Colour	Black

#### Packaging

Outer Quantity	200
Outer Dimensions (inches)	19x14x13
Weight Uom	25.8 lbs. per 100

#### Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)