



Actual

Catalog Number: GRNY-250-0-C
Product ID: 7TAG009750R0034
UPC Number: 72849411670
EAN Number: 05414363023685
Status: Active

Extruded Grommeting, Black Nylon 6.6 for Temperatures up to 85 Degrees Celsius (185 F), Height of 7.11mm (0.28 Inches), Width of 9.40mm (0.37 Inches), Thickness 1.27mm (0.05 Inches), Width Maximum Panel Thickness of 6.35mm (0.25 Inches)

- Used to line panel edges and knockouts where the chafing of wires is a concern.
- Available in 8 stock sizes in 100-ft. lengths for panels from .040 - .250 inches thick and in a variety of stocked materials to cover a wide range of applications.
- Application Tools: SR-100

North American Specifications (UNSPSC)

UNSPSC	39131603 Grommet edging
IGCC	5393 Grommet edging
Brand Name	Catamount
Type	Grommeting
Special Features	Used to line panel edges and knockouts where the chafing of wires is a concern.
Color	Black
Panel Thickness	0.250
Material	Nylon/Polyamide 6.6

European Specifications (ETIM)

ETIM	EC000879 Feed through spout
For wall thickness	6.35-6.35mm
Total length	30480mm
Model	Open
Shrink technique	N
Angle model	N
Material	Plastic
Material quality	Polyamide
Surface protection	Untreated
Halogen free	Y
Colour	Black
Gastight	N
Fire resistant	Y
Watertight	N

Packaging

Inner Quantity	1
Inner Dimensions (inches)	21x15x2.25
Outer Quantity	5
Outer Dimensions (inches)	18x12.5x12
Weight Uom	2 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet Canada Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321

