




Actual



Representative

Catalog Number: H050GRSST
Product ID: 7TBD013740R0000
UPC Number: 78621000271
EAN Number: 05415022257786
Status: Active

1/2 Inch 316 Stainless Steel Grounding Hub, Thermoplastic Insulating Throat, Sealing Ring Nitrile (BUNA-N) for Use with Rigid/IMC Conduit

- Suitable for hazardous locations use in Class I, Division 2; Class II, Division 1 & 2; Class III, Division 1 & 2 per NEC 501-4(b); 502-4 (a) and 503-3 (a)
- Suitable for hazardous locations use in Class II, Groups E, F, G & Class III locations per CEC 18-202; 18-252; 18-302; 18-352.
- Meets NEMA sealing requirements for NEMA 3R, 4, 4X and 13 enclosures

North American Specifications (UNSPSC)

UNSPSC	39131707 Electrical conduit coupling
IGCC	5548 Electrical conduit coupling
Brand Name	T&B
Type	Grounding Hub
Special Features	Hexagonal/Splined Body and Locknut Enable Fast and Easy Installation
Application	For Use with Rigid/IMC Conduit
Standard	UL E23018, CSA
Trade Size	1/2 Inch
Outside Diameter	1.44 Inch
Length	1.56 in
Material	316 Stainless Steel

European Specifications (ETIM)

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	1/2 inch
Model	Straight
Revolving thread	N
Connection type screw connection to housing	Thread
Thread type	NPT
Material housing	Stainless steel

Packaging

Inner Quantity	25
Inner Dimensions (inches)	6.24x4x4
Outer Quantity	100
Outer Dimensions (inches)	12.75x9x5
Weight Uom	25 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com