

Explosion-Proof Flexible Couplings



Technical Specifications

Reference	Thread Type (inch)	Flexible Length (mm)	Dimensions (mm)	
			A	B
XPLFL16	1/2 NPT	150	39.1	36.6
XPLFL18	1/2 NPT	200	39.1	36.6
XPLFL110	1/2 NPT	250	39.1	36.6
XPLFL112	1/2 NPT	300	39.1	36.6
XPLFL115	1/2 NPT	380	39.1	36.6
XPLFL118	1/2 NPT	460	39.1	36.6
XPLFL124	1/2 NPT	610	39.1	36.6
XPLFL212	3/4 NPT	300	40.6	47.5
XPLFL215	3/4 NPT	380	40.6	47.5
XPLFL218	3/4 NPT	460	40.6	47.5
XPLFL224	3/4 NPT	610	40.6	47.5
XPLFL236	3/4 NPT	915	40.6	47.5
XPLFL318	1 NPT	460	50.08	58.7

Explosion-Proof and Dust- Ignition-Proof for Use in Hazardous Locations.

T&B® XP Flex™ Couplings make it easy to achieve tight bends in conduit systems in confined spaces - or to connect stationary equipment to equipment that moves or vibrates. Their explosion-proof and corrosion-resistant construction mean you can use them with confidence in hazardous and wet locations.

