

Representative

Catalog Number: 2702

 Product ID:
 7TAD105040R0014

 UPC Number:
 78621002702

 EAN Number:
 05414363140269

Status: Active

Liquidtight Cord Connector, 1-1/4 Inch, Straight, Cord Range 0.890 to 1.090 Inch, Meets Coast Guard CG293, Nylon, Black

- Segmented chuck provides high mechanical pullout performance, will not cut or damage cord jacket.
- Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC. Class I, Div 2; Class II, Div 1 & Elist II, Div 1 & Elist III, Di
- Meets Coast Guard CG293

North American Specifications (UNSPSC)		
UNSPSC	39121431 Cable gland connector	
IGCC	4601 Cable gland connector	
Brand Name	T&B	
Туре	Cord Connectors-Straight	
Special Features	Hand Tightens, No Tools Needed for Assembly	
Application	To Connect Flexible Cord to a Box or Enclosure	
	and Provide Adequate Strain Relief.	
Standard	UL E13938, CSA	
Size	1-1/4 Inch	
Conductor Range	0.890 to 1.090 Inch	
Material	Nylon	
Color	Black	
Temperature Rating	-34 to +105 Degrees C	

European Specifications (ETIM)		
ETIM	EC000441 Cable screw gland	
Thread type	NPT	
Nominal thread size inch/gas pipe thread	1 1/4 inch	
Thread length	19.84mm	
Suitable for cable diameter	22.606-27.686mm	
Material	Plastic	
Material quality	Polyamide (PA)	
Colour	Black	
Model	Straight	
Operating temperature	-34-+105°C	

Packaging	
Inner Quantity	2
Inner Dimensions (inches)	5x4.5x3
Outer Quantity	10
Outer Dimensions (inches)	10.9x8.6x5.4
Weight Uom	33.5 lbs. per 100

Documents / Support Tools	
Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet	TA01320-TB2

3D Model Available on Website



For further technical assistance, please contact us...

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com