



Actual

Catalog Number: FG-DA-3/8
Product ID: 7TAD013950R0001
UPC Number: 78620969862
Status: Active

Drain Adapter, 3/8 Inch, UL Type 4X Listed and NSF Certified for Food and Beverage, 1.38 Inch Length, 0.75 Inch Diameter, 1/4 Inch NPT Thread for Drain Adaptor Assembly Connection, 316 Stainless Steel

T&B's new stainless steel drain adapter provides an easy-to-install, UL® Listed drain point at any ordinary location of the electrical system where threaded connections are not possible. A stainless steel ball valve can be assembled to the drain adapter to provide the convenience of controlling and inspecting the drainage process, and by closing the valve, the assembly becomes suitable for wash-down areas.

- The drain adaptor and ball valve are NSF Certified for food and beverage applications.
- When the drain adapter is used in conjunction with the T&B ball valve, the assembly offers a UL Type 4X rating and is suitable for wash down areas.
- The adapter and valve are both constructed of Type 316 Stainless Steel for superior corrosion resistance.
- The innovative, compact body design and special-grade silicone gasket make the drain adapter suitable for installation in tight spaces and on curved surfaces.
- Large drain orifices, an integral breather, and no moving parts ensures long-lasting performance without clogging, even when exposed to viscous liquids or small debris.
- Both the drain adaptor and the ball valve offer a "female NPT threaded connection for assembling a drain tube to direct the liquid removal.
- Provides an easy-to-install, UL Listed drain point at any ordinary location of the electrical system where threaded connections are not possible

North American Specifications (UNSPSC)

UNSPSC	39131708 Electrical conduit fitting body
IGCC	5563 Electrical conduit fitting body
Brand Name	T&B
Type	Drain for Food and Beverage
Special Features	Compact Body Design and Special-Grade Silicone Gasket Make the Drain Adapter Suitable for Installation in Tight Spaces and on Curved Surfaces
Application	Conduit Drain
Standard	cULus Listed 4X, NSF Certified when used with Ball Valve
Hub Size	3/8 Inch
Length	1.38 in
Width	0.75 in
Material	316 Stainless Steel

Packaging

Inner Quantity	1
Inner Dimensions (inches)	3x.2x5
Outer Quantity	5
Outer Dimensions (inches)	3.4x2.4x4.7
Weight Uom	0.09 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-001158
Instruction Sheet	TA04757-TB2
Marketing Brochure US	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com