



Actual

Catalog Number: LH75
Product ID: 7TAD105350R0012
UPC Number: 03448115288
Status: Active
Replacement Catalog: NCG-0752B

Cord Grip with NPT Threads, Locknut Included, NPT Thread Size 3/4 Inch, Cable Range 0.450 Inch/11.4mm to 0.709 Inch/18.0mm, Hole Clearance 1.068 Inch/27.1mm, Thread Length 0.63 Inch/16.0mm, IP68 Rating, Nylon, Black

- New threads on body prevent skipping, faster installation.
- All nylon construction with TPE gland resists salt water, weak acids, gasoline, alcohol, oil, grease and common solvents.
- Suitable for NEMA type 4 and 6 enclosures.
- Working temperatures: -22 degrees F (-30 degrees C) to 212 degrees F (100 degrees C). For short periods to 302 degrees F (150 degrees C).

North American Specifications (UNSPSC)

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	Carlton
Type	Cord Grips-Straight
Special Features	New Threads on Body Prevent Skipping, Faster Installation
Application	Suitable for NEMA Type 4 and 6 Enclosures
Standard	UL E13938
Size	3/4 Inch
Conductor Range	0.450 Inch/11.4mm to 0.709 Inch/18.0mm
Material	Nylon
Color	Black
NEMA Rating	4, 6
Temperature Rating	-30 to +100 Degrees C

European Specifications (ETIM)

ETIM	EC000441 Cable screw gland
Thread type	NPT
Nominal thread size inch/gas pipe thread	1/2 inch
Thread length	16.0mm
Suitable for cable diameter	11.4-18.0mm
Material	Plastic
Material quality	Polyamide (PA)
Degree of protection (IP)	IP68
Colour	Black
Model	Straight
Operating temperature	-30-+100°C

Packaging

Inner Quantity	50
Inner Dimensions (inches)	6.375x6.375x6.75
Outer Quantity	400
Outer Dimensions (inches)	14.25x14.25x14.75
Weight Uom	0.06 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-AC03717
--------------------------------	-------------

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com