



Actual



Representative

**Catalog Number:** 2690  
**Product ID:** 7TAD105030R0007  
**UPC Number:** 78621002690  
**EAN Number:** 05414363140221  
**Status:** Active

Liquidtight Cord Connector, 1/2 Inch, Straight, Cord Range 0.125 to 0.275 Inch, Meets Coast Guard CG293, Nylon, Black

- Segmented chuck provides high mechanical pullout performance, will not cut or damage cord jacket.
- Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC. Class I, Div 2; Class II, Div 1 & 2; Class III, Div 1 & 2; NEC 501-4(b), 502-4(a)(b), 503-3(a)(b)
- Meets Coast Guard CG293

#### North American Specifications (UNSPSC)

|                    |  |
|--------------------|--|
| UNSPSC             | 39121431 Cable gland connector   |
| IGCC               | 4601 Cable gland connector   |
| Brand Name         | T&B  |
| Type               | Cord Connectors-Straight   |
| Special Features   | Hand Tightens, No Tools Needed for Assembly  |
| Application        | To Connect Flexible Cord to a Box or Enclosure and Provide Adequate Strain Relief. |
| Standard           | UL E13938, CSA   |
| Size               | 1/2 Inch   |
| Conductor Range    | 0.125 to 0.275 Inch  |
| Material           | Nylon  |
| Color              | Black  |
| Temperature Rating | -34 to +105 Degrees C  |

#### European Specifications (ETIM)

|  |                            |
|--|----------------------------|
| ETIM                                     | EC000441 Cable screw gland |
| Thread type                              | NPT                        |
| Nominal thread size inch/gas pipe thread | 1/2 inch                   |
| Thread length                            | 15.08mm                    |
| Suitable for cable diameter              | 3.175-6.985mm              |
| Material                                 | Plastic                    |
| Material quality                         | Polyamide (PA)             |
| Colour                                   | Black                      |
| Model                                    | Straight                   |
| Operating temperature                    | -34-+105°C                 |

#### Packaging

|                           |                  |
|---------------------------|------------------|
| Inner Quantity            | 25               |
| Inner Dimensions (inches) | 6x4.5x3          |
| Outer Quantity            | 100              |
| Outer Dimensions (inches) | 12.9x6.8x5.4     |
| Weight Uom                | 4.5 lbs. per 100 |

#### Documents / Support Tools

|                                       |                      |
|---------------------------------------|----------------------|
| Technical Drawing / Data Sheet US     | Available on Website |
| Technical Drawing / Data Sheet Canada | Available on Website |
| Instruction Sheet                     | TA01320-TB2          |

#### Header

|          |                      |
|----------|----------------------|
| 3D Model | Available on Website |
|----------|----------------------|

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)