



Representative

**Catalog Number:** 376LR-J5240-S  
**Product ID:** 7TAA121300R0038  
**UPC Number:** 78378629322  
**Status:** Active

35kV 200 Amp, Loadbreak Elbow Connector with Test Point, Cable Insulation Diameter 0.980 inch to 1.180 inch. Bi-Metal Compression Lug. Conductor Size AWG Compressed Stranded 1/0 /Solid 2/0 /mmSquared 53.49. 200ECS Jacket Seal Included.

## North American Specifications (UNSPSC)

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Elastimold
Type	Loadbreak Elbow Connector with Test Point
Special Features	35kV, 200 Amp Loadbreak Elbow. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Provision for hot stick operation. Provision for ground wire connection. Non-Corrosive Capacitive Voltage Test Point.
Application	35 kv, 200 Amp
Standard	ANSI/IEEE Standard 386
Size	Cable Insulation Diameter 0.980 inch to 1.180 inch.
Connection	Push-in
Conductor Range	Conductor Size AWG Compressed Stranded 1/0 / Solid 2/0 /mmSquared 53.49.
Material	Housing - EPDM Rubber
Color	Black
Voltage Rating	35kV
Amperage Rating	200 Amps
Insulation	Yes, EPDM Rubber
Temperature Rating	-20 Degrees C to +65 Degrees C
Environmental Conditions	Fully Submersible
Consist Of	1 Elbow Connector Housing, 1 Compression Lug, 1 Probe, 1 Probe Wrench, 1 Tube Lubricant, 1 Crimp Chart, 1 V.D. Cap-Peroxide, 1 Installation Instruction Sheet

## Packaging

Outer Quantity	8
Outer Dimensions (inches)	19.13x14.5x14
Weight Uom	3.1 lbs. Each

## Documents / Support Tools

Technical Drawing / Data Sheet	Available on Website
Instruction Sheet	Available on Website
Support/Tools	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)