



Representative

Catalog Number: 1602A3R
Product ID: 7TAA121150R0000
UPC Number: 78378646946
Status: Active

15kV 200 Amp, Loadbreak Feed-Thru Insert, Fully rotatable for 360 degree positioning. Includes bail assembly to secure feed-thru insert to bushing well.

North American Specifications (UNSPSC)

UNSPSC	26121630 Cable accessories
IGCC	1779 Cable accessories
Brand Name	Elastimold
Type	Feed-Thru Insert
Special Features	15kV, 200 Amp Loadbreak Rated. Transform radial feed transformer into loop-feed unit. Provide extra tap for elbow arrester connection. Peroxide-cured insulation and jacket. Provision for groundwire connection. Fully rotatable for 360 degree positioning. Includes bail assembly to secure feed-thru insert to bushing well.
Application	Designed for use as an apparatus bushing interface and provide extra tap connection.
Standard	ANSI/IEEE 386
Size	10.66 inch (270.8 mm) Length, 4.00 inch (101.6 mm) Center to Center, 7.00 inch (177.8 mm) wide.
Material	EPDM Rubber
Temperature Rating	- 40 Degrees C to 65 Degrees C

Packaging

Inner Quantity	1
Outer Quantity	5
Outer Dimensions (inches)	19x13x9
Weight Uom	4.62 lbs. Each

Documents / Support Tools

Instruction Sheet	Available on Website
Catalog Canada	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com