



Line Art

Catalog Number: C749N 5/8 EG
Product ID: 7TAA005950R0003
UPC Number: 61601311653
Status: Active

Brace, Seismic, Length 4-1/2 Inches, Height 2-3/8 Inches, Width 1-5/8 Inches, Hole Diameter 11/16 Inches, Load Safety Factor 1,650 Pounds, Electro-Galvanized Steel

- All braces have plasticol coating on the flat member which insulates against vibration noise transmission and eliminates rattle at the connection points

North American Specifications (UNSPSC)

UNSPSC	39121701 Electrical hangers
IGCC	5026 Electrical hangers
Brand Name	Superstrut
Type	Pipe Straps, Pipe Clamps & Hangers (Series 700)
Special Features	All braces have plasticol coating on the flat member which insulates against vibration noise transmission and eliminates rattle at the connection points
Application	For use in seismic bracing applications
Material	Steel
Finish	SilverGalv/Electro-Galvanized

Packaging

Outer Quantity	25
Outer Dimensions (inches)	7.5x7.5x6.62
Weight Uom	68.75 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
-----------------------------------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com