



Representative

Catalog Number: CTPA08/100M
Product ID: 7TCA298000R0026
EAN Number: 05020963022821
Status: Active

Lightweight Weight, Extra Flexible Conduit, NC Size 08/NW Size 7.5, Outside Diameter 10.0mm, Inside Diameter 6.5mm, Static Bend Radius 10mm, High Fatigue Life and Abrasion, Impact Resistance, IP40 Rating, Polyamide 6, Reel Length 100 Meters, Black

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5540 Flexible Non-Metallic Conduit
Brand Name	Harnessflex
Type	Lightweight Conduit
Special Features	Self Extinguishing, Low Smoke Toxicity & Halogen Free
Application	General Purpose, Lightweight Loom Applications
Standard	RoHS, Conforms with end of life vehicle directive (ELV)EU200/53/EC
Trade Size	NC08/NW7.5
Outside Diameter	10.0mm
Inside Diameter	6.5mm
Length	100 m
Radius	Static Bend Radius 10mm
Flexibility	High
Material	Polyamide/Nylon 6
Color	Black

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	8mm
Nominal size in inch	1/8 inch
Outer diameter	10mm
Inner diameter	6.5mm
Material	Polyamide 6
Operating temperature	-40-+120°C
Degree of protection (IP)	IP40
Fire resistance in accordance with UL94	HB
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Halogen free	Y

Packaging

Inner Quantity	1
Inner Dimensions (inches)	17x37x17
Outer Quantity	8
Outer Dimensions (inches)	17x37x17
Weight Uom	3.75 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com