



Representative

Catalog Number: EXMU-1
Product ID: 7TAD013670R0018
UPC Number: 04226934580
Status: Active

1/2 Inch Male to Female Union, Die Cast Aluminum, for Hazardous and Non Hazardous Locations

- Precision NPT threaded hubs allow trouble-free field installation for rigid or IMC conduit.
- Unique concentric ring design insures critical flame path control

North American Specifications (UNSPSC)

UNSPSC	39131707 Electrical conduit coupling
IGCC	5548 Electrical conduit coupling
Brand Name	T&B
Type	Three-Piece Couplings
Special Features	Precision Cast and Machined Surfaces Permit Safer Wire Pulling.
Application	Connecting Elements Between Enclosures, Fittings, or Boxes Which Permit Future Changes to the System In Both Hazardous and Non-Hazardous Areas
Standard	UL E34438, CSA
Trade Size	1/2 Inch
Material	Steel

European Specifications (ETIM)

ETIM	EC000939 Coupler for installation tubes
Material	Metal
Material quality	Aluminium
Model	Thread
Two piece	N
With inspection opening and cover	N

Packaging

Inner Quantity	5
Inner Dimensions (inches)	5.63x4x2.44
Outer Quantity	25
Outer Dimensions (inches)	13.38x6.25x4.88
Weight Uom	32.38 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com