



Actual

**Catalog Number:** H1/0-PS-C  
**Product ID:** 7TAI029620R0095  
**UPC Number:** 78621089086  
**Status:** Active

Non-Insulated Parallel Splice, Length .750 Inches, Outer Diameter .571 Inches, Inner Diameter .446 Inches, Wire Range 1/0 AWG, 83,700kcmil-119,500kcmil, Copper, Tin Plated

- Resistant to corrosion and preserve the electrical integrity of the wires in single or multiple strands.
- Feature an intelligent constructable part number for quick identification of the wire range.
- Application Tools: TBM750M1, TBM8750BSCR

## North American Specifications (UNSPSC)

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Sta-Kon
Type	Splice Connector
Special Features	Resistant to corrosion and preserve the electrical integrity of the wires in single or multiple strands. Feature an intelligent constructable part number for quick identification of the wire range.
Standard	UL E9809
Material	Copper
Finish	Tin Plated
Color	Metallic
Voltage Rating	600V

## European Specifications (ETIM)

ETIM	EC001059 Crimp splices for copper conductor
AWG-range	1/0-1/0
Material	Copper
Surface protection	Tinned
Insulation	None

## Packaging

Inner Quantity	100
Inner Dimensions (inches)	4x4x3
Outer Quantity	1000
Outer Dimensions (inches)	21.5x8.5x3.43
Weight Uom	2.5 lbs. per 100

## Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000229
Technical Drawing / Data Sheet Canada	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)