



Representative

**Catalog Number:** KNF18-187-20FDM  
**Product ID:** 7TAI029190R0100  
**UPC Number:** 78621010792  
**Status:** Active

Nylon Insulated Female Disconnect, Length .795 Inches, Width .197 Inches, Tab Size .187x.020, Wire Range #22-#16 AWG, Color Red, Copper, Tin Plated

- Fully Insulated. Metal Insulation Sleeve. Molded Insulator. Internal Barrel Serrations. Funnel Entry.
- Application Tools: WT112M, CM2000A

## North American Specifications (UNSPSC)

UNSPSC	39121447 Wire terminal disconnect
IGCC	4667 Wire terminal disconnect
Brand Name	Spec-Kon
Type	Disconnects
Special Features	Fully Insulated. Metal Insulation Sleeve. Molded Insulator. Internal Barrel Serrations. Funnel Entry.
Application	For use in temporary connections to male disconnects and terminal blocks.
Standard	UL E66716
Material	Brass with Copper Sleeve
Color	Red
Insulation	Nylon

## European Specifications (ETIM)

ETIM	EC000516 Round or flat plug/receptacle
Nominal cross section	0.5-1.5mm <sup>2</sup>
Insulation	Partially Insulated
Colour insulation	Red
Material insulation	PA
Material	Copper

## Packaging

Inner Quantity	1000
Inner Dimensions (inches)	7x5x3.25
Outer Quantity	10000
Outer Dimensions (inches)	7x5x3.2
Weight Uom	1.9 lbs. per 1000

## Documents / Support Tools

Technical Drawing / Data Sheet US Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)