



Actual

Catalog Number: L4/0-PS-L
Product ID: 7TAI029630R0104
UPC Number: 78621089092
Status: Active

Non-Insulated Parallel Splice, Length .770 Inches, Outer Diameter .766 Inches, Inner Diameter .629 Inches, Wire Range 4/0 AWG 190,000kcmi-231,100kcmil, Copper, Tin Plated

- Resistant to corrosion and preserve the electrical integrity of the wires in single or multiple strands.
- Feature an intelligent constructable part number for quick identification of the wire range.
- Application Tools: TBM750M1, TBM8750BSCR

North American Specifications (UNSPSC)

UNSPSC	39121449 Wire or cable compression splice
IGCC	4669 Wire or cable compression splice
Brand Name	Sta-Kon
Type	Splice Connector
Special Features	Resistant to corrosion and preserve the electrical integrity of the wires in single or multiple strands. Feature an intelligent constructable part number for quick identification of the wire range.
Standard	UL E9809
Material	Copper
Finish	Tin Plated
Color	Metallic
Voltage Rating	600V

European Specifications (ETIM)

ETIM	EC001059 Crimp splices for copper conductor
Material	Copper
Surface protection	Tinned
Insulation	None

Packaging

Inner Quantity	50
Inner Dimensions (inches)	4x4x3
Outer Quantity	500
Outer Dimensions (inches)	21.5x9x4
Weight Uom	3.94 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000229
Technical Drawing / Data Sheet Canada	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com