



Actual

Catalog Number: SL-5
Product ID: 7TAA123920R0004
UPC Number: 78378662919
EAN Number: 05415022249286
Status: Active

5.3 oz. Silicone lubricant for high voltage electrical work.

- Excellent dielectric properties
- Excellent oxidation resistance
- Excellent water repellency
- Resistant to a variety of chemicals
- Compatible with most plastics and rubbers
- Use in the most harsh environments
- Silicone compound is a specially formulated grease product containing selected silicone oils and inert silica fillers.
- This stiff, tacky compound has excellent dielectric properties, oxidation resistance and water repellency.
- It is essentially non-toxic and non-melting and retains its pliability even after extended service.

North American Specifications (UNSPSC)

UNSPSC	39121337 Electrical sealing compound
IGCC	4496 Electrical sealing compound
Brand Name	Elastimold
Type	Lubricant
Special Features	Specially Formulated for High Voltage Cable.
Application	Heavy Duty Electrical Applications
Size	5.3 oz
Container	Tube
Form	Cream
Material	Silicone Rubber

Packaging

Outer Quantity	24
Outer Dimensions (inches)	11.5x7.9x8.8
Weight Uom	37.5 lbs. per 100

Documents / Support Tools

Technical Drawing / Data Sheet US	Available on Website
Safety Data Sheet (SDS) Global	SDS-00031-TB2

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com