

**Catalog Number:** CPO-A-1500-48  
**Product ID:** 7TAA017320R0010  
**UPC Number:** 78621025299  
**Status:** Active



Thin-Wall Heat-Shrinkable Tubing for Cable Range , Expanded Diameter 1.5 inch, Length 48 inches, rated for 600 Volt, 125 degrees C, Material: Cross-linked polyolefin - Adhesive Lined, Black

- Adhesive lined for moisture-proof environmental seal.
- High 3:1 shrink ratio for covering irregularly shaped objects.

Actual

## North American Specifications (UNSPSC)

|                  |   |
|------------------|---|
| UNSPSC           | 39121723 Heat shrinkable tube                         |
| IGCC             | 5073 Heat shrinkable tube                             |
| Brand Name       | Shrink-Kon  |
| Type             | Thin-Wall Heat-Shrinkable Tubing                      |
| Special Features | Adhesive lined for moisture-proof environmental seal. |
| Shrink Ratio     | 3:1   |
| Thickness        | Thin  |
| Length           | 48 in   |
| Color            | Black   |

## European Specifications (ETIM)

|                                   |                        |
|-----------------------------------|------------------------|
| ETIM                              | EC000217 Shrink tubing |
| Type                              | Heat-shrink            |
| Model                             | Thin-walled            |
| Shrink rate                       | 3:1                    |
| Inner diameter before heat-shrink | 38mm                   |
| Inner diameter after heat-shrink  | 12.954mm               |
| Nominal diameter inch             | 1 1/2 inch             |
| Wall thickness after shrinking    | 1.016mm                |
| Length                            | 1.22m                  |
| Operation temperature             | -55-+110°C             |
| Colour                            | Black                  |
| Material                          | Polyolefin (PO-X)      |
| Halogen free                      | N                      |
| With inner glue                   | Y                      |
| Printable                         | N                      |
| UL approval                       | N                      |

## Packaging

|                           |                 |
|---------------------------|-----------------|
| Outer Quantity            | 25              |
| Outer Dimensions (inches) | 8.375x49x10.875 |
| Weight Uom                | 39 lbs. per 100 |

## Documents / Support Tools

|                                       |                      |
|---------------------------------------|----------------------|
| Technical Drawing / Data Sheet Canada | Available on Website |
| Safety Data Sheet (SDS) Global        | SDS-00046-TB2        |

For further technical assistance, please contact us...

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)