



Representative

**Catalog Number:** 9306  
**Product ID:** 7TCD012330R0042  
**UPC Number:** 78621009306  
**EAN Number:** 05414363076155  
**Status:** Active

5/16 Inch ISO Metric Thread Insulated Liquidtight Connector, Steel to Galvanized,. Chromate Finish. Metric ISO Thread Size 16 for Use With Flexible Metal Conduit

**North American Specifications (UNSPSC)**

UNSPSC	39121420 Liquid tight connectors
IGCC	4585 Liquid tight connectors
Brand Name	T&B Industrial Fitting
Type	Liquidtight Flexible Metal Conduit Fittings
Special Features	UL Listed Liquidtight
Size	5/16 Inch
Material	Nylon Insulated

**European Specifications (ETIM)**

ETIM	EC001180 Screw connection for protective metallic hose
Nominal size in inch	5/16 inch
Model	Straight
Revolving thread	N
Construction type	External thread
Connection type screw connection to housing	Thread
Thread type	Metric
Thread connection size	M16 x 1.5
One-piece	N
Material housing	Steel
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UL	Y

**Packaging**

Inner Quantity	25
Outer Quantity	300
Outer Dimensions (inches)	15.5x9.6x6.9
Weight Uom	6.25 lbs. per 100

**Documents / Support Tools**

Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website

**Header**

3D Model	Available on Website
----------	----------------------

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
www.tnb.com

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com