

Catalog Number: 3303SL
Product ID: 7TAA106090R0004
UPC Number: 78621093392
Status: Active

3/4 Inch Non-Metallic Sheathed Cable - Two Screw Connector with Slotted Head Screw, For Non-Metallic Sheathed Cables 8/2, 8/3 or 6/2, For Multiple (2) NM Cables 12/2 or 14/3, For Flexible Cords Cable Opening .530 Inch to .835 Inch, For Multiple Flexible Cords (.530 Combined Diameter Minimum) (2) 18/3 Minimum, For Service Entrance Cables Minimum Opening .395 Inch X .622 Inch

North American Specifications (UNSPSC)

UNSPSC	39121419 Flex connectors
IGCC	4573 Flex connectors
Brand Name	T&B Fittings
Type	Non-Metallic Sheathed Cable Conduit Fittings
Special Features	Rounded Cable Grip and Smooth Bushing Protect The Cable Sheath and Wire Insulation, Since Saddle is Threaded, Screws Do Not Travel or Extend Beyond The Connector Body As It is Clamped to The Cable, An Extra Lip on The Saddle Closes The Unused Part of The Connector Opening.
Size	3/4 Inch
Connection	Straight
Material	Steel
Finish	Electro Zinc Plated
Color	Metallic

European Specifications (ETIM)

ETIM	EC001178 Screw connection for protective plastic hose
Nominal size in inch	3/4 inch
Model	Straight
Revolving thread	N
Construction type	External thread
Type of connection	Other
Thread connection size	Other

Packaging

Inner Quantity	50
Inner Dimensions (inches)	8.25x5.25x4.25
Outer Quantity	250
Outer Dimensions (inches)	21x5.5x8.62
Weight Uom	11.19 lbs. per 100

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com