

Actual



Representative

Catalog Number: 2684

Product ID: 7TAD105040R0004 **UPC Number:** 78621002684

Status: Active

 $\label{linear} \mbox{Liquidtight Cord Connector, 3/4 Inch, 90 Degree Bend, Cord Range 0.660 to 0.780 Inch, \\ \mbox{Meets Coast Guard CG293, Nylon, Black}$

- Segmented chuck provides high mechanical pullout performance, will not cut or damage cord jacket.
- Temperature Rating: -34 to +105 Degrees Celsius
- Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC. Class I, Div 2; Class II, Div 1 & Div 1
- Meets Coast Guard CG293

North American Specifications (UNSPSC)			
UNSPSC	39121431 Cable gland connector		
IGCC	4601 Cable gland connector		
Brand Name	T&B		
Туре	Cord Connectors-90 Degree		
Special Features	Hand Tightens, No Tools Needed for Assembly		
Application	To Connect Flexible Cord to a Box or Enclosure		
	and Provide Adequate Strain Relief.		
Standard	UL E13938, CSA		
Size	3/4 Inch		
Conductor Range	0.660 to 0.780 Inch		
Material	Nylon		
Color	Black		
Temperature Rating	-34 to +105 Degrees C		

European Specifications (ETIM)		
ETIM	EC000441 Cable screw gland	
Thread type	NPT	
Nominal thread size inch/gas pipe thread	3/4 inch	
Thread length	15.49mm	
Suitable for cable diameter	16.764-19.812mm	
Material	Plastic	
Material quality	Polyamide (PA)	
Colour	Black	
Model	90°-elbow	
Operating temperature	-34-+105°C	

Packaging	
Inner Quantity	10
Inner Dimensions (inches)	8x5x4
Outer Quantity	50
Outer Dimensions (inches)	17x14x4.75
Weight Uom	15.19 lbs. per 100

Documents / Support Tools	
Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet	TA01320-TB2

Header	
3D Model	Available on Website



For further technical assistance, please contact us...

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com