

**Catalog Number:** K655BVS  
**Product ID:** 7TAA122800R0000  
**UPC Number:** 78378663947  
**Status:** Active



Actual

15/25kV 600 Series Deadbreak Vault Stretcher (Housing Only with Stud)

#### North American Specifications (UNSPSC)

UNSPSC	26121630 Cable accessories
IGCC	1779 Cable accessories
Brand Name	Elastimold
Type	Vault Stretcher Housing
Special Features	Fully rated 15/25kV, 600 Amp Deadbreak Vault Stretcher. Fully shielded, fully submersible molded rubber housing. 100 percent peroxide-cured construction includes insulation and conductive EPDM materials. Can be easily connected or disconnected using standard hand tools and equipment in a de-energized state. Optional accessories allow visible external separation, by-pass, isolation, dead-ending, grounding, and testing as well as adding taps, surge arrestors, and fault current indicators.
Application	The K655BVS vault stretcher housing is a component of the Vault Stretcher product line.
Standard	ANSI/IEEE Standard 386
Size	2.50 inch (63.5 mm) Diameter. 21.75 inch (552.50 mm) Length. Centerline to Edge 10.88 inch (276.2 mm)
Material	EPDM Rubber

#### Packaging

Outer Quantity	1
Outer Dimensions (inches)	23x9x4
Weight Uom	6.55 lbs. Each

#### Documents / Support Tools

Technical Drawing / Data Sheet	Available on Website
Instruction Sheet	Available on Website
Catalog Canada	Available on Website

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
www.tnb.com

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: techsupport@tnb.com