Thomas&Betts



Actual



Representative

Catalog Number: Product ID: UPC Number: Status:

2694 7TAD105040R0011 78621002694 Active

Liquidtight Cord Connector, 3/4 Inch, Straight, Cord Range 0.400 to 0.560 Inch, Meets Coast Guard CG293, Nylon, Black

- Segmented chuck provides high mechanical pullout performance, will not cut or damage cord jacket.
- Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC. Class I, Div 2; Class II, Div 1 & amp; 2; Class III, Div 1 & amp; 2; NEC 501-4(b), 502-4(a)(b), 503-3(a)(b)
- Meets Coast Guard CG293

North American Specifications (UNSPSC)

UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	T&B
Туре	Cord Connectors-Straight
Special Features	Hand Tightens, No Tools Needed for Assembly
Application	To Connect Flexible Cord to a Box or Enclosure
	and Provide Adequate Strain Relief.
Standard	UL E13938, CSA
Size	3/4 Inch
Conductor Range	0.400 to 0.560 Inch
Material	Nylon
Color	Black
Temperature Rating	-34 to +105 Degrees C

Furencen Crecifications (FTIM)			
European Specifications (ETIM)			
ETIM	EC000441 Cable screw gland		
Thread type	NPT		
Nominal thread size inch/gas pipe thread	3/4 inch		
Thread length	15.875mm		
Suitable for cable diameter	10.16-14.224mm		
Material	Plastic		
Material quality	Polyamide (PA)		
Colour	Black		
Model	Straight		
Operating temperature	-34-+105°C		
Packaging			
Inner Quantity	25		
Inner Dimensions (inches)	8.2x5.2x4.4		
Outer Quantity	100		
Outer Dimensions (inches)	16.6x10.8x6.4		
Weight Uom	6.5 lbs. per 100		
Documents / Support Tools			
Technical Drawing / Data Sheet US	Available on Website		
Technical Drawing / Data Sheet Canada	Available on Website		

Header

Instruction Sheet

3D Model

Available on Website

TA01320-TB2



Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@thb.com