



Family

Catalog Number: TNF18-4MB-XV
Product ID: 7TAI029350R0154
UPC Number: 72849414490
EAN Number: 05414363492153
Status: Active

Fully Insulated Nylon Male Bullet Disconnects for Wire Range 22-16 , Red

- Fully Insulated. Metal Insulation Sleeve. Molded Insulator. Internal Barrel Serrations. Funnel Entry.
- Application Tools: WT112M, CM2000C

North American Specifications (UNSPSC)

| | |
|------------------|---|
| UNSPSC | 39121447 Wire terminal disconnect |
| IGCC | 4667 Wire terminal disconnect |
| Brand Name | Catamount |
| Type | Disconnects |
| Special Features | Fully Insulated. Metal Insulation Sleeve. Molded Insulator. Internal Barrel Serrations. Funnel Entry. |
| Standard | UL E9809 |
| Material | Brass with Copper Sleeve |
| Color | Red |
| Insulation | Nylon |

Packaging

| | |
|---------------------------|-----------------|
| Inner Quantity | 75 |
| Inner Dimensions (inches) | 50.59x3.29x3.11 |
| Outer Quantity | 900 |
| Outer Dimensions (inches) | 10.5x10x8 |
| Weight Uom | 5 lbs. per 1000 |

Documents / Support Tools

| | |
|---------------------------------------|----------------------|
| Technical Drawing / Data Sheet US | Available on Website |
| Technical Drawing / Data Sheet Canada | Available on Website |

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com