



Representative

Catalog Number: HS40-400-25
Product ID: 7TAA017100R0012
UPC Number: 78621077613
EAN Number: 05414363152842
Status: Active

Heavy-Wall Heat-Shrinkable Tubing for Cable Range 2/0 - 350 MCM, Expanded Diameter 1.5 inch. Length 25 feet reel, rated for 600 Volt, 90 degree continuous use, Material: Cross-linked polyolefin with thermoplastic adhesive liner, Black

- Made of thermally stabilized cross-linked polyolefin, enabling a recovered wall thickness greater than that of the cable jacket replaced.
- Withstands severe mechanical requirements of U.R.D., submersible, and direct burial installations.

North American Specifications (UNSPSC)

UNSPSC	39121723 Heat shrinkable tube
IGCC	5073 Heat shrinkable tube
Brand Name	Shrink-Kon
Type	Heavy-Wall Heat-Shrinkable Tubing
Special Features	Made of thermally stabilized cross-linked polyolefin, enabling a recovered wall thickness greater than that of the cable jacket replaced.
Voltage Rating	600V
Length	25 ft
Color	Black

European Specifications (ETIM)

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thick-walled
Shrink rate	3:1
Inner diameter before heat-shrink	38.1mm
Inner diameter after heat-shrink	11.938mm
Nominal diameter inch	1 1/2 inch
Wall thickness after shrinking	3.5566mm
Length	7.62m
Operation temperature	-55-+110°C
Colour	Black
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	N

Packaging

Outer Quantity	1
Outer Dimensions (inches)	13x6x13
Weight Uom	4.88 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000473
Technical Drawing / Data Sheet Canada	Available on Website
Safety Data Sheet (SDS) Global	SDS-00046-TB2

For further technical assistance, please contact us...

Memphis, TN 38120
www.tnb.com

860 Ridge Lake Blvd.
Memphis, TN 38120

Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com