

Representative

Catalog Number: 2677

 Product ID:
 7TAD105040R0002

 UPC Number:
 78621002677

 EAN Number:
 05414363140184

Status: Active

Liquidtight Cord Connector, 1 Inch, Straight, Cord Range 0.770 to 0.895 Inch, Meets Coast Guard CG293, Nylon, Black

- Segmented chuck provides high mechanical pullout performance, will not cut or damage cord jacket.
- Suitable for use in hazardous locations where general purpose equipment is specifically permitted by NEC. Class I, Div 2; Class II, Div 1 & Elist II, Div 1 & Elist III, Di
- Meets Coast Guard CG293

North American Specifi	ications (UNSPSC)
UNSPSC	39121431 Cable gland connector
IGCC	4601 Cable gland connector
Brand Name	T&B
Туре	Cord Connectors-Straight
Special Features	Hand Tightens, No Tools Needed for Assembly
Application	To Connect Flexible Cord to a Box or Enclosure
	and Provide Adequate Strain Relief.
Standard	UL E13938, CSA
Size	1 Inch
Conductor Range	0.770 to 0.895 Inch
Material	Nylon
Color	Black
Temperature Rating	-34 to +105 Degrees C

European Specifications (ETIM)			
ETIM	EC000441 Cable screw gland		
Thread type	NPT		
Nominal thread size inch/gas pipe thread	1 inch		
Thread length	19.84mm		
Suitable for cable diameter	19.558-22.733mm		
Material	Plastic		
Material quality	Polyamide (PA)		
Colour	Black		
Model	Straight		
Operating temperature	-34-+105°C		

Packaging	
Inner Quantity	10
Inner Dimensions (inches)	8x5x4
Outer Quantity	100
Outer Dimensions (inches)	16.6x14x8.9
Weight Uom	17.13 lbs. per 100

Documents / Support Tools	
Technical Drawing / Data Sheet US	Available on Website
Technical Drawing / Data Sheet Canada	Available on Website
Instruction Sheet	TA01320-TB2

Head	er
------	----

3D Model Available on Website



For further technical assistance, please contact us...

Thomas & Betts - USA 860 Ridge Lake Blvd. Memphis, TN 38120 www.tnb.com T&B Technical Support MS 3B-50 860 Ridge Lake Blvd. Memphis, TN 38120 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com