



Representative

Catalog Number: 168FLR1-C0220
Product ID: 7TAA124110R0031
UPC Number: 78378679688
Status: Active

Molded Current Limiting Fuse Housing, Nominal Fuse Voltage Rating 8.3kV, Fuse Test Port - Two Capacitive Test Ports, Small Housing, Cable Insulation Diameter 0.805 inch - 1.060 inch / 20-27mm, Aluminum Conductor size 2 AWG Stranded/Compressed, 1 AWG Solid/Compact.

North American Specifications (UNSPSC)

UNSPSC	39121421 Electrical connector assembly
IGCC	4586 Electrical connector assembly
Brand Name	Elastimold
Type	Loadbreak Fused Elbow Connector
Special Features	Full-Range Current-Limiting Fusing with 50kA Interrupting Capability. Hotstick Operable 15kV Load-break Elbow Switching.
Application	Protect Light Duty Underground Distribution Systems
Standard	IEEE 386, ANSI C37.40, ANSI C37.41, ANSI C37.47
Size	Length 16.87 inches from bottom to center of Bushing
Conductor Range	#2 Stranded Compressed, #1 Solid Compact
Material	EPDM Rubber
Color	Black
Voltage Rating	8.3kV
Amperage Rating	200 Amps
Insulation	Yes, EPDM Rubber
Temperature Rating	-20 Degrees C to +65 Degrees C

Packaging

Outer Quantity	1
Outer Dimensions (inches)	11.5x4.75x14.5
Weight Uom	1 lbs. Each

Documents / Support Tools

Technical Drawing / Data Sheet	Available on Website
Instruction Sheet	Available on Website
Support/Tools	Available on Website
Catalog US	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA
 860 Ridge Lake Blvd.
 Memphis, TN 38120
www.tnb.com

T&B Technical Support
 MS 3B-50
 860 Ridge Lake Blvd.
 Memphis, TN 38120

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com