



Representative



Representative

**Catalog Number:** 03700270  
**Product ID:** 7TAA122010R0009  
**UPC Number:** 78378666368  
**EAN Number:** 05415022341201  
**Status:** Active

15/25/35kV 600 Amp Series Deadbreak Compression Lug (Tin-Plated Aluminum). Conductor Size AWG Compressed/Stranded 4/0, or kcmil Compacted/Solid 250. Length 5.94 inches. Diameter 1.38 Inches. 1-Hole Pad, .50 inch Thick. Hole Size .688 inch Diameter.

## North American Specifications (UNSPSC)

UNSPSC	39121405 Cable or wire lug
IGCC	4532 Cable or wire lug
Brand Name	Elastimold
Type	Compression Lug
Special Features	Tin Plated Aluminum. Hole Size .688 inch. Connectors can used with both Copper and Aluminum Conductors.
Application	Used with 15/25/35kV 600 Amp Deadbreak Elbow and Splice products.
Cable Size	Conductor Size kcmil Compressed or Stranded 500, or Compacted or Solid 600.
Number Of Holes	1
Amperage Rating	600 Amps
Voltage Rating	15/25/35kV
Insulation	None
Material	Aluminum
Color	Silver
Connection	Compression
Size	Length 5.94 inch, Diameter 1.38 inch, Hole .688 inch Diameter.

## European Specifications (ETIM)

ETIM	EC001053 Crimp cable lug for aluminium conductors
Material	Aluminium
Number of fixing holes	1

## Packaging

Outer Quantity	1
Outer Dimensions (inches)	19.25x15x8.25
Weight Uom	0.31 lbs. Each

## Documents / Support Tools

Technical Drawing / Data Sheet	Available on Website
Support/Tools	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
 MS 3B-50  
 860 Ridge Lake Blvd.  
 Memphis, TN 38120

Hours: 7AM - 6PM CDT  
 Monday-Friday  
 Phone: (888) 862-3289  
 Fax: (901) 252-1321  
 Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)