



Actual

**Catalog Number:** COND1/2-G  
**Product ID:** 7TAA087020R0000  
**UPC Number:** 70450826101  
**EAN Number:** 05415022251258  
**Status:** Active

PVC Coated Conduit, Pipe Size 1/2 Inch/16 Metric, Outside Diameter with PVC .92 Inch/ 23.30 Millimeters, Nominal Wall Thickness with PVC .14 Inch/3.56 Millimeters, Length without Couplings 9 Feet 11-1/4 Inch/3.03 Meters, Hot-dip Galvanized Steel, Gray

- A minimum .040 inch (40 mil) PVC coating on the exterior.
- A nominal .002 inch (2 mil) blue urethane on the interior.
- Color coded thread protectors on each end.
- Blue urethane coating over Hot-Dip Galvanized threads.

### North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5535 Electrical conduit
Brand Name	Ocal
Type	Conduit-PVC Coated
Special Features	Color-Coded Thread Protectors
Application	Corrosion Protection for Electrical Systems
Standard	cULus E46453, CSA
Trade Size	1/2 Inch
Outside Diameter	0.92 Inch/23.30mm
Inside Diameter	0.63 Inch/16.10mm
Length	9.94 ft ; 3.03 m
Material	Steel
Finish	Hot-Dip Galvanized
Wall Thickness	0.14 Inch/3.56mm
Color	Gray

### European Specifications (ETIM)

ETIM	EC001179 Protective metallic hose
Nominal size in inch	1/2 inch
Outer diameter	23.30mm
Inner diameter	21.30mm
Material	Steel
Surface protection	Other
Sheathing material 2nd coating (exterior)	PVC
Colour	Grey
Bending strength	Rigid

### Packaging

Inner Quantity	10
Outer Quantity	1000
Outer Dimensions (inches)	120x20x6
Weight Uom	0.9 lbs. Each

### Documents / Support Tools

Technical Drawing / Data Sheet	WSD-000042
Technical Drawing / Data Sheet Canada	Available on Website
Support/Tools	Available on Website
Catalog US	Available on Website

For further technical assistance, please contact us...

Thomas & Betts - USA  
860 Ridge Lake Blvd.  
Memphis, TN 38120  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
860 Ridge Lake Blvd.  
Memphis, TN 38120

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)